barrplastics.com



1.800.665.4499

# Marine Buoys

#### **Standard Mooring Buoys**

Buoys can be used to mark waterways, can be rented to boaters at your marinas, or can be used to support the line to which you anchor your own watercraft. Our cost-effective orange-striped standard mooring buoys match Transport Canada regulations for private moorage and will remain durable and attractive for years to come.

The hard polyethylene shell on our mooring buoys has UV inhibitors to keep it looking new, while the polystyrene foam fills the shell to provide maximum buoyancy. A PVC tube is molded through the center of the buoy to allow for different hardware options and an injection-molded collar captures the tube on each end and protects the buoy from wear.



#### Eyelet Hardware Style

Attach directly to mooring line BELOW the buoy.

Part #	Description	Diameter (in)	Buoyancy (lbs)	Thru Tube ID (in)	Weight (lbs)
FFMB1212TCA	Eyelet Hardware Style Buoy	12	30	1.75	4
FFMB2424TCA	Eyelet Hardware Style Buoy	24	248	1.75	16
FFMB1818TCA	Eyelet Hardware Style Buoy	18	102	1.75	8



### Thru-Chain & Shackle Style

#### Attach directly to shackle at the TOP of the buoy.


Part #	Description	Diameter (in)	Buoyancy (lbs)	Thru Tube ID (in)	Weight (lbs)
FFMB1818TC	Thru Chain Style Buoy	18	51	2.75	8
FFMB2424TC	Thru Chain Style Buoy	24	124	2.75	16
FFMB3232TC	Thru Chain Style Buoy	32	278	2.75	41
FFMB3838TC	Thru Chain Style Buoy	38	556	2.75	65
FFMB4242TC	Thru Chain Style Buoy	42	710	2.75	86

#### Thru-Chain Style W/ Extended Pipe

Attach directly to shackle at the TOP of the pipe.

Part #	Description	Diameter (in)	Buoyancy (lbs)	Thru Tube ID (in)	Weight (Ibs)	
FFMB1818EP	Thru Chain Extend. Pipe Buoy	18	51	2.75	8	
FFMB2424EP	Thru Chain Extend. Pipe Buoy	24	124	2.75	16	-
FFMB3232EP	Thru Chain Extend. Pipe Buoy	32	278	3.5	41	
FFMB3838EP	Thru Chain Extend. Pipe Buoy	38	556	3.5	65	9
FFMB4242EP	Thru Chain Extend. Pipe Buoy	42	710	3.5	86	20









## Contact BARR Plastics Today!

barrplastics.com | 1.800.665.4499



	Part #	Description	Buoy Size Needed (in)	Working Load Limit (lbs)	Weight (lbs)
Style	FFMB12F	12" Galvanized Eyelet Assembly	12	N/A	2
let S	FFMB18F	18" Galvanized Eyelet Assembly	18	N/A	3
Eyelet	FFMB24F	24" Galvanized Eyelet Assembly	24	N/A	4
	SHACKLE580	5/8" Shackle - Galv. for 1/2" Mooring Chain	18-24	6500	1
Style	SHACKLE750	3/4" Shackle - Galv. for 3/4" Mooring Chain	18-42	9500	2
Shackle St	SHACKLE780	7/8" Shackle - Galv. for 3/4" Mooring Chain	32-42	N/A	4
8	BUOYCHAIN500	1/2" Hot-Dip Galv. Long Link Mooring Chain	18-24	4500	2 lbs./ft.
u Chain	BUOYCHAIN750	3/4" Hot-Dip Galv. Long Link Mooring Chain	24 -42	10000	3.5 lbs./ft.
Thru	BCB500	3" HD UV Plastic Aligning Washer- for 1/2" Chain	18-24	N/A	0.2
	BCB750	4" HD UV Plastic Aligning Washer- for 3/4" Chain	24-42	N/A	0.3



