celebrating 50 years

PLASTICS TANKS & LIQUID HANDLING

PRODUCT CATALOGUE



BARR Plastics Inc | 1.800.665.4499 | info@barrplastics.com | barrplastics.com

TABLE OF CONTENTS

Aboveground Plastic Tanks

Small Vertical Storage Tanks 4
Large Vertical Storage Tanks 5
Transport Tanks 6-10
Applicator, Inductor, Total Drain, Spot Sprayer Tanks .. 11
Inductor Stands & Applicator Saddle Assemblies 12
Black or Dark Green Water Tanks 13
Specialty Water Tanks 14
Chemical Injection Tanks 15
Cone Bottom Tanks 16-17
Lids & Fittings 18-22

Belowground Plastic Tanks

Septic Tanks & Accessories 23-24
Belowground Holding Tanks & Accessories 25-26

Commercial Grade Plastic Tanks

Vertical Bulk Storage Tanks 27-29
Horizontal Bulk Storage Tanks & Accessories 30-33
Elliptical Tanks 34
Round Horizontal Bulk Storage Tanks 35
Cone Bottom Bulk Storage Tanks 36-37
Inductor Tanks 38
Batch Tanks 39
Open Top Containment Tanks 40
Pickup Tanks 41
Spot Sprayer Tanks 42
Stackable Totes 43
Pallet Paks 44
Specialty Bulk Storage & Applicator Tanks 45-46
PCO (Pest Control Operator) Tanks 47





TABLE OF CONTENTS

Commercial Grade Plastic Tanks (Cont'd)

Water Only Vertical Tanks 48
Septic/Cistern Tanks & Accessories 49-50
Tractor Mounted Tanks 51
Crop Care Tanks 52

Accessory Parts

Fittings 53
Lids & Spinwelds 54

Utility Tanks

T-Tanks / Box-Shaped Tanks 55
Open Top Liquid Storage Tanks 56

Valves & Couplers

Ball Valves 57-59
Couplers, Adapters, Switch Adapters 60-61
King Nipples & Hose Barbs 62
Flange Ball Valves & Fittings 63-64
SCH80 Polypropylene Fittings 65-67
Y-Line & T-Line Strainers 68-69
Lids, Lid Accessories, & Repair Kits 70
Poly Bulkhead Fittings/EPDM or Viton Gaskets 71-72
Bolted Fittings 73-78







Aboveground Plastic Tanks

Small Vertical Storage Tanks

BARR Plastics is a master distributor of molded poly tanks, manufactured by Norwesco. Norwesco tanks are manufactured to strict quality guidelines to ensure years of high-performance use. Rugged, impact-resistant, one-piece seamless polyethylene construction make them suitable for the storage and/or transport of most liquid chemicals.

Gallon Capacity	Diameter	Overall Height	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
22	20	20	8	3/4"	43608	-
25	18	29	5	3/4"	41867	-
50	18	53	5	3/4"	41865	-
65	23	43	8	1 1/4"	45192	-
75	23	49	8	1 1/4"	41863	-
100	28	43	8	1 1/4"	41861	-
105	23	63	8	2"	40803	-
120	38	31	5	1 1/4"	40318	-
150	30	56	8	1 1/4"	41859	-
165	31	56	16	2"	40281	-
200	30	72	8	2"	41856	-
210	32	67	16	2"	47401	-
220	42	44	5	1 1/4"	40320	-
250	30	89	8	2"	41854	-
300	35	79	16	2"	40213	-
305	46	50	16	2"	40302	-
310	32	94	16	2"	43625	-
500	48	73	16	2"	40148	40150
550	67	44	16	2"	40023	-
750	48	103	16	2"	40606	-
850	48	118	16	2"	42214	-
1000	64	80	16	2"	40251	40154
1100	87	53	16	2"	40070	40081
1100 G	87	53	16	2"	42591	42593
1500	64	116	16	2"	40144	40146
1550	87	67	16	2"	40235	40236
1550 G	87	67	16	2"	42595	42597
1700	87	74	16	2"	40010	40012

Aboveground Plastic Tanks

Large Vertical Storage Tanks

Norwesco vertical tanks feature tie-down slots, built-in graduated gallon indicators, an offset fill-opening and a self-vented, slosh-proof lid. Most frequently used for bulk storage and mobile nursing applications.

Gallon Capacity	Diameter	Overall Height	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
2000	64	152	16	2″	47109	47564
2100	87	89	16	2″	40178	40241
2100	102	69	16	2″	41399	-
2500	95	91	16	2″	40051	40052
2500	102	79	22	2″	42382	42384
2550	93	95	16	2″	43816	43818
3000	91	119	16	2″	45081	-
3000	95	109	16	2″	40754	40755
3000	95	109	16	3″/2″	43092	43093
3000	102	93	16	2″	45246	42380
3000	102	93	22	2″	43136	43138
4000	102	125	16	3″/2″	40312	-
4200	102	131	16	3″/2″	41403	-
5000	102	152	16	3″/2″	40164	40166
5000	141	86	16	3″/2″	40941	43833
5500	138	92	16	3″/2″	45086	-
5800	141	100	16	3″/2″	40071	43820
6000	102	182	16	3″/2″	40226	40233
6100	119	140	16	3″/2″	40659	40661
6500	119	150	16	3″/2″	40224	40232
6500	120	147	16	3″/2″	42315	42317
7800	119	176	16	3″/2″	40663	40665
8400	119	188	16	3″/2″	42060	42062
9000	141	146	16	3″/2″	40543	40231
9000	141	146	22	3″/2″	43618	43620
10000	141	160	16	3″/2″	40545	40353
10000	141	160	22	3″/2″	43128	43130
12000	141	193	16	3″ *	40539	40541
15000	141	244	16	3″ *	41334	41336
15000	165	186	22	3″ *	43821	43823
20000	165	242	22	3″ *	43825	43827

Aboveground Plastic Tanks

Transport Tanks

Horizontal Leg Tanks

With the broadest leg tanks line available, Norwesco manufactures a size that will fit your needs. Used primarily for transport and nursing applications, Norwesco's leg tanks feature molded-in legs that act as "baffles" to reduce sloshing.

Gallon Capacity	Diameter (in)	Overall Height (in)	Length (in)	Fill Opening (in)	Outlet/ Drain (in)	No. of Bands	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
35	20	23	29	5	3/4	2 optional	45223	-
55	23	26	34	5	3/4	2 optional	41873	-
65	23	26	43	5	3/4	2 optional	45191	-
125	32	35	41	8	2	2 optional	40298	-
225	38	41	49	8	2	2 optional	40299	-
225 Stand	38 W	41	45	-	-	-	42854	-
325	38	43	68	16	2	2 optional	40217	-
330	38	40	74	5	2	2 optional	42923	-
425	49	54	60	16	2	2 optional	42016	-
525	49	54	71	16	2	2 optional	40181	40193
725	49	54	101	16	2	3 optional	40180	40194
925	62	65	80	16	2	2 optional	45209	-
925	62	69	80	16	2	2 optional	45210	-
1025	49	54	139	16	2	4 optional	40089	40131
1325	66	70	99	16	2	3 optional	41875	41877
1625	63	68	139	16	2	4 optional	40026	40133
1800	62	68	146	16	2	4 optional	42990	-
1800	62	72	146	16	2	4 optional	42992	-
5025	92	96	190	16	3/2	5 optional	41879	41881





Aboveground Plastic Tanks

Transport Tanks

Elliptical Leg Tanks

This elliptical tank style is designed to provide the greatest capacity with the lowest center of gravity, making it the best design available for transporting larger volumes. Norwesco elliptical tanks feature molded-in legs that act as "baffles" to reduce sloshing and provide increased stability during transport. Norwesco elliptical leg tanks require full length bottom support as well as support bands. The 1600 flat bottom requires full length bottom support but does not require bands.

Gallon Capacity	Width (in)	Overall Height (in)	Length (in)	Fill Opening (in)	Outlet/Drain (in)	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
335	48	33	71	16	2	42339	-
535	57	39	80	16	2	42353	-
1035	79	54	89	16	2	40191	-
1235	66	53	128	16	2	40239	-
1335	66	55	126	16	2	42927	42929
1600	80	53	126	16	2	43143	43167
1635	71	58	142	16	2	40387	40388
2035	84	56	142	16	2	40618	40623
2635	90	72	140	16	3/2	40547	40283
3135	88	80	150	16	3/2	40686	40688
4035	92	75	192	16	3/2	41267	41269

Drainable Leg Tanks

They are designed primarily for use on fertilizer and chemical nurse trailers. All Norwesco drainable tanks require full length bottom support as well as support bands. Suitable when complete drainage is necessary.

Gallon Capacity	Width (in)	Overall Height (in)	Length (in)	Fill Opening (in)	Outlet/Drain (in)	No. of Bands	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
710	47	57	104	16	2	3 required	40655	40657
1010	47	58	140	16	2	4 required	40393	40395
1310	66	75	99	16	-	3 required	41871	41872
1315	66	60	126	16	-	3 required	42925	42926
1610	69	63	140	16	-	4 required	40806	40808
2010	69	74	140	16	-	4 required	43651	43652
2610	90	79	140	16*	-	4 required	41382	41383
3210	92	75	178	16*	-	4 required	40822	40824

* 16" hinged lid

Aboveground Plastic Tanks

Transport Tanks

Whether using the tank in a stationary position or for transport, bands are necessary to ensure that the tank retains its shape and integrity.

Horizontal Leg Tank Bands

Tank Size	A (in)	B (in)	C (in)	No. of Bands	Part No.
35	18 1/2	18 1/2	21 3/8	2 optional	60520
55	22	22	26 1/2	2 optional	61745
65	22	22	26 1/2	2 optional	61745
125	30 3/4	30 1/2	35	2 optional	61744
225	36 1/2	36	42	2 optional	60478
325	36 1/2	36	42	2 optional	60478
330	36 1/2	36	42	2 optional	60478
425	47 3/4	46 1/4	52 1/4	2 optional	600575
525	47 3/4	46 1/4	52 1/4	2 optional	600575
725	47 3/4	46 1/4	52 1/4	3 required	600575
925	61	60	66	2 required	62852
1025	47 3/4	46 1/4	52 1/4	4 required	600575
1325	64	64	70	3 required	63282
1625	61	60 3/4	67 1/4	4 required	60079
1800*	61	60	66	4 required	62852
5025	89 3/4	89 1/2	93 7/8	5 required	63284

Ladders

Description	Tank Size	Part No.
Ladder (optional)	2635 & 3135	60354
Ladder (optional)	2610 & 3210	63047
Ladder (optional)	4035	63033
Adaptor kit for ladder*	3135	62301

* This kit is required when using the ladder on the 3135 gallon tank

Drainable Leg Tank Bands

Tank Size	A (in)	B (in)	C (in)	No. of Bands	Part No.
710	46 1/4	45	51	3 required	60584 short
1010*	46 1/4	45	51	2 required	60584 short
1010*	48	45	51	2 required	60585 long
1310	64	64	70	3 required	63282
1315	49 3/4	63 1/2	69 1/2	3 required	63642
1610	49	66	72	4 required	62434
2010	59	66	72	4 required	63846
2610*	58	87 1/2	91 7/8	2 required	63044 short
2610*	62	87 1/2	91 7/8	2 required	63045 long
3210*	56	89 1/2	92 3/4	2 required	62347 short
3210*	60	89 1/2	92 3/4	2 required	62348 long

* 2 short and 2 long bans are required for 1 tanks.

Steel Supports & Accessories for Leg Tanks
Elliptical Leg Tank Bands

Tank Size	A (in)	B (in)	C (in)	No. of Bands	Part No.
335	29	46 1/2	52 1/2	2 required	63546
535	35	55 1/2	61 1/2	2 required	63547
1035	47 1/4	77	83	3 required	60325
1235	47 3/4	34 3/4	70 3/4	4 required	60477
1335	49 3/4	63 1/2	69 1/2	3 required	63642
1635	51	68	74	4 required	60586
2035	51 1/4	81 1/2	86 3/4	4 required	62079
2635	65 1/4	87 1/2	94	4 required	60353
313*	75 1/4	85 1/2	92	4 required	62097
3135**	74 1/4	85 1/2	92	4 required	63620
4035	70 1/4	89 1/2	96	4 required	62832

* for tanks manufactured in CA, MN, OK, TX, UT
** for tanks manufactured in GA, OH

Aboveground Plastic Tanks

Transport Tanks

Pickup Truck Tanks

Designed to fit full-size, American made pickups, the 325 and 425 sizes have low profiles for better rear vision. They feature fill openings offset to the side of the tank safety and easy access. A tough circular design adds strength.

Gallon Capacity	Top Width or Diameter (in)	Bottom Width or Diameter (in)	Overall Height	Fill Opening (in)	Outlet/Drain (in)	Premium Weight Part No. (White)
210*	60/51	48/39	29	8	2	40300
325	62	49	33	8	2	40160
425	65	49	39	8	2	40102

* 210 gallon tank fits both "mini" pickups and full-size models.

Flat Bottom Utility Tanks

Like the PCO tank, the flat bottom utility tank can be used for many applications. It is the perfect choice when looking for a tank to put in the bed of a pickup truck. The tank may be used with or without bands.

Gallon Capacity	Width	Height	Length	Fill Opening	Outlet/ Drain	Part #
26	18	20	25	8"	3/4"	43835
45	18	22	38	5"	1"	43837
50	19	23	38	8"	1"	42341
52	24	15	43	5"	1"	43839
68	27	17	42	5"	1"	43841
100	27	29	43	8"	1"	42343
110	35	18	48	5"	1"	42349
150	36	29	48	8"	1"	42345
200	36	38	48	8"	1"	42347

Flat Bottom Utility Tank Bands

Tank Size	A	B	C	No. of Bands	Part No.
50	19	18 1/2	23	2 optional	63551
100	24	25	29 1/2	2 optional	63552
150	24	34 1/2	39	2 optional	63553
200	33	34 1/2	39	2 optional	635543

PCO Tanks

The PCO is well suited for nursery, agricultural and lawn care applications. These tanks feature self-supporting legs and do not require any saddles or steel supports. Flat spots are molded into both ends to provide mounting areas for agitation equipment.

Gallon Capacity	Width	Overall Height	Length	Fill Opening	Part #
Smooth Wall					
30	19	23	25	5	41254
50	19	22	38	8	40664
100	30	28	38	8	40668
150	36	28	48	8	40669
200	36	37	48	8	41413
300	36	37	69	16	41381
Ribbed					
50	19	23	38	8	42834
100	30	30	38	8	42835
150	37	29	48	16	42836
200	37	37	48	16	42837

Aboveground Plastic Tanks

Transport Tanks

Loaf Tanks

Loaf tanks are designed for a variety of applications. Its rectangular shape allows for placement within pickup beds or it may be mounted on various equipment trailers for use as a mobile water supply. This line of tanks may also be used in a variety of stationary storage applications.

Gallon Capacity	Width	Overall Height	Length	Fill Opening	Premium Weight Part No. (White)
50	27″	17″	41″	8″	43610
100	27″	30″	41″	8″	43611
200	36″	29″	48″	8″	43612
300	42″	30″	63″	8″	43613
500	48″	31″	92″	8″	43843



Elliptical Tanks


Designed for larger volume applicator needs, the Norwesco elliptical tanks feature a low profile design and a low center of gravity for excellent visibility in the field and increased stability when towed. A deep sump
permits complete drainage and the tanks feature an 8″ or 16″ fill-opening. Skid not included with tank.

Gallon Capacity	Width	Overall Height incl. Sump	Length	Sump Depth	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)
200	40″	30″	66″	3/4″	8″	1 1/4″ & 1 1/4″	41252
300	48″	36″	70″	3″	16″	1 1/4″ & 1 1/4″	40327
500	57″	44″	82″	5″	16″	1 1/4″ & 1 1/4″	40328
750	69″	48″	88″	3″	16″	2″	40329
1000	78″	55″	90″	3″	16″	2″	40330
1600*	78″	54″	138″	2 1/2″	16″	2″	47111

* Includes 1 stainless steel baffle

Elliptical Tank Skids

Tank Size	Tank Part #	A	B	C	D	E	F	Part #
200	41252	4″	24″	52″	57″	2″ x 68″	8″	63015
300	40327	4″	34″	46 1/4″	54 1/4″	2″ x 76″	8″	63016
500	40328	4″	34″	60″	68″	2″ x 96″	8″	63018
750	40329	4″	38″	69 1/2″	78″	2″ x 112″	8″	60371
1000	40330	4″	46″	60″	72″	2″ x 130″	8″	60372



Aboveground Plastic Tanks

Applicator, Inductor, Total Drain, & Spot Sprayer Tanks

Applicator Tanks

All Norwesco applicator tanks feature a lid which threads directly into the fill-opening of the tank to prevent the sloshing or leaking of tank contents during transport or application. The inductor tanks are suitable for mixing chemicals when filling a tank. The spot sprayers feature threaded inserts on the bottom of the tank for mounting purposes, on one side for wand/gun placement and on the top for a 12 volt pump. Please refer to page 9 for steel supports.

Gallon Capacity	Diameter	Height	Length	Fill Opening	Outlet/Drain	Part #
20	15	18	31	5″	3/4″	61737
30	23	26	21	5″	3/4″	41799
55	23	27	34	5″	3/4″	45193
85	23	26	52	5″	3/4″	45105
100	24	28	57	8″	3/4″	60204
110	30	34	41	8″	1 1/4″ & 1 1/4″	45053
150	30	33	58	8″	1 1/4″ & 1 1/4″	40648
150	32	35	46	8″	1 1/4″ & 1 1/4″	45117
200	32	35	62	8″	1 1/4″ & 1 1/4″	45059
200	38	42	47	8″	1 1/4″ & 1 1/4″	45061
300	38	41	68	8″	1 1/4″ & 1 1/4″	40135
400	42	45	74	8″	1 1/4″ & 1 1/4″	40137
500	48	51	75	8″	1 1/4″ & 1 1/4″	40274
150 Slim	28	41	50	8″	1 1/4″ & 1 1/4″	40777
200 Slim	24	48	61	8″	1 1/4″ & 1 1/4″	41305
200 Slim	31	46	48	8″	1 1/4″ & 1 1/4″	40780

Spot Sprayer Tanks

Gallon Capacity	Diameter	Height	Fill Opening	Outlet/ Drain	Part #
14	14	15	5″	-	45115
25	18	18	5″	-	62080

Total Drain Tanks

Gallon Capacity	Diameter	Height	Fill Opening	Outlet/ Drain	Part #
5 square	11	18	8	1 1/4″	42321
10 square	13	21	8	1 1/4″	42351
12 square	14	15	5	3/4″	60521

Inductor Tanks

Gallon Capacity	Diameter	Height	Fill Open-ing	Outlet/ Drain	Part #
15	19	23	8	2″	60214
15	24	21	16	2″	42064
30	24	28	16	2″	42065
35	23	29	8	2″	45098
60	31	32	16	2″	62205
60	24	42	16	2″	42066
80	32	37	16	2″	47190




Aboveground Plastic Tanks


Inductor Stands and Applicator Saddle Assemblies

Designed to provide necessary support for the applicator/inductor tank during use. Norwesco saddles include polyester straps, buckles and bolts to secure tanks, and inductor stands are supplied with all necessary hardware.

Inductor Tank Stands

Tank Size	Tank part No.	A	B	Part No.
15 x 19"D	60214	15 1/2"	38"	60313
15 x 24"D	42064	13 1/2"	36"	63397
30 x 24"D	42065	13 1/2"	43"	63397
35 x 23"D	45098	15	44"	65517
60 x 31"D	62205	14 1/2"	47"	62204
60 x 24"D	42066	13 1/4"	56"	63397





Applicator Tank Saddle Assemblies

Tank Size	Tank Part No.	A	B	C	D	E	F	G	Part No.
30	41799	3"	19"	13 1/2"	13 1/2"	2" x 54"	8"	7 3/4"	60321
55	45193	6"	18 1/8"	24"	24"	2" x 48"	-	12"	60303
85	45105	6"	18 1/8"	24"	24"	2" x 48"	-	12"	60303
110	45053	12"	23 3/4"	28 3/4"	34 3/4"	2" x 72"	-	10 3/4"	60315
150-30"	40648	12"	23 3/4"	28 3/4"	34 3/4"	2" x 72"	-	10 3/4"	60315
150-32"	45117	12"	23 3/4"	28 3/4"	34 3/4"	2" x 72"	-	10 3/4"	60315
200-32"	45059	6"	24 7/8"	36"	60"	2" x 96"	8"	13 1/4"	63019
200-38"	45061	6"	24 3/4"	34"	42"	2" x 96"	-	13 1/4"	63020
300-38"	40135	6"	24 3/4"	34"	60"	3" x 96"	8"	12"	63021
400-42"	40137	6"	30 1/8"	42 1/2"	60"	3" x 96"	8"	12"	63022
500-48"	40274	6"	30 1/8"	42 1/2"	60"	3" x 132"	8"	12"	63023

Aboveground Plastic Tanks

Black or Dark Green Water Tanks

Our water tanks are manufactured using resins that meet FDA specifications to ensure safe storage of potable water. The black or green colour limits light penetration, which reduces the growth of waterborne algae. These tanks are rated at 8 pounds per gallon, which means that they are for WATER STORAGE ONLY! They should not be used for chemicals, fertilizers, or any other product. Where applicable, the tanks will carry the NSF approval. Please contact BARR Plastics for more specific information regarding NSF approval.



Gallon Capacity	Diameter	Overall Height	Fill Opening	Bottom Fitting	Top Fitting
12	38″	31″	5″	2″	1 1/2″
165	31″	56″	16″	2″	1 1/2″
220	42″	44″	5″	2″	1 1/2″
305	46″	50″	16″	2″	1 1/2″
500	48″	73″	16″	2″	1 1/2″
550	67″	44″	16″	2″	1 1/2″
600	64″	50″	8″	2″	1 1/2″
1000	64″	80″	16″	2″	1 1/2″
1075	87″	57″	8″	2″	1 1/2″
1100	87″	53″	16″	2″	1 1/2″
1350	71″	88″	16″	2″	1 1/2″
1500	95″	58″	16″	2″	1 1/2″
1525	93″	62″	8″	2″	1 1/2″
1550	87″	67″	16″	2″	1 1/2″
2500	95″	91″	16″	2″	1 1/2″
2500	102″	79″	16″	2″	1 1/2″
2500	102″	79″	22″	2″	1 1/2″
2550	93″	95″	16″	2″	1 1/2″
3000	95″	109″	16″	2″	1 1/2″
3000	102″	93″	16″	2″	1 1/2″
3000	102″	93″	22″	2″	1 1/2″
5000	102″	152″	16″	2″	1 1/2″
5000 Peanut Can	119″	112″	22″	2″	1 1/2″
5000 Tuna Can	141″	86″	16″	2″	1 1/2″
5000 Tuna Can	141″	86″	22″	2″	1 1/2″
6500	119″	150″	16″	2″	1 1/2″
10000	141″	160″	16″	2″	-
10000	141″	160″	22″	2″	-

Aboveground Plastic Tanks

Specialty Water Tanks

Low Profile Water Tanks

The low profile tanks may be used for storage or transport. They are an excellent choice when eight limitations are a factor and are the perfect heigh for putting under your cottage or cabin.

Gallon Capacity	Width	Overall Height	Length	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)
1250	81″	38″	130″	16″	2″	40756
1275	84″	36″	126″	16″	2″	43011
1500	81′	44″	130″	16″	2″	41392
1600	84″	42″	126″	16″	2″	43013
2400	90″	53″	150″	16″	2″	40912

Free Standing Water Tanks

These tanks have been specifically designed with residential and commercial applications in mind. The dimensions of the tanks allow them to fit through a conventional doorway. The design of the freestanding/self-supporting tanks eliminate the need for a steel support frame.

Gallon Capacity	Width	Overall Height	Length	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)
250	29″	40″	62″	16″	1 1/4″	42337
300	29″	48″	62″	16″	1 1/4″	41869
400	29″	70″	66″	16″	1 1/4″	43856
400	30″	68″	63″	16″	1 1/4″	41247
500	31″	70″	74″	16″	1 1/4″	43616

Containment Basins/Tanks

Our containment basins and tanks are impact and corrosion resistant and are molded as a one-piece, seamless unit. The 140, 250, 360, 500, 600, and 1300 gallon sizes are “basin style”; the 1350 is an open top tank and the 2050 and 2800 “Tank In A Tank” ar emolded with a doem that can be cut off to enable them to be used as a containment tank. Required containment capacity may vary depending on application and location.

Gallon Capacity	Width/ Diameter	Overall Height	Length	Fill Opening	Outlet/ Drain	Premium Weight Part No.	Colour
125 w/ stand *	48″ diameter	60″	-	8″	1″ SS fitting	43161	White Tank/ Black Stand
140	45″	17″	45″	-	-	42771	Black
250	68″	11″	92″	-	-	42114	Black
360	69″	16″	93″	-	-	42940	Black
500	80″	19″	92″	-	-	42051	Black
600	84″	20″	98″	-	-	43069	Black
1300	97″	22″	175″	-	-	42195	Black
1350	87″ diameter	53″	-	-	-	42052	White
2050 **	102″ diameter	82″	-	16″	-	43072	White
2800 **	102″ diameter	104″	-	16″	-	42222	White

Aboveground Plastic Tanks

Chemical Injection Tank Systems

Our chemical injection tank system is designed for applications in the oil and gas industry. The package includes a leg tank, stand, and enclosed containment basin. The enclosed containment basins have a pump mount, a 2″ and a 3″ female threaded connection for additional items such as solar panels.

Gallon Capacity	Length	Width	Height	Fill Opening	Part No.
125 Chemical Injection System (tank, stand, basin)					63880
125 Leg Tank	43 1/2″	32″	35 1/2″	6″	
Stand for 125 Leg Tank	30 1/4″	32″	32″	6″	
Containment Basin - 165 Gallon	64″	45″	14 1/2″	6″	
225 Chemical Injection System (tank, stand, basin)					63885
225 Tank - Leg Tank	52″	38″	41 1/2″	6″	
Stand for 225 Leg Tank	34 1/2″	38″	30″	6″	
Containment Basin - 300 Gallon	89″	54″	15 1/2″	6″	
325 Chemical Injection System (tank, stand, basin)					63890
325 Tank - Leg Tank	56″	44″	49″	6″	
Stand for 325 Leg Tank	34 1/2″	38″	30″	6″	
Containment Basin - 380 Gallon	80″	54″	19 1/2″	6″	



Aboveground Plastic Tanks

Cone Bottom Tanks

BARR Plastics offers a full range of cone bottom tanks designed for a variety of applications. The conical bottoms enable quick and complete drainage. As with all Norwesco tanks, the cone bottom tanks are molded of rugged, high density polyethylene and are both impact and chemical resistant. Please refer to page 16 for polyethylene or steel stands.





Gallon Capacity	Slope	Diameter	Overall Height	Fill Opening	Outlet/Drain	Premium Weight Part No. (White)	Heavy Weight Part No. (Blue)
160	45	36″	52″	16″	2″	43845	-
160	45	36″	51″	16″	2″ female pipe thread	43847	-
175 w/stand*	30	43″	49″/9″***	16″	2″	60113	-
300	45	48″	56″	16″	2″	43848	-
300 w/stand*	30	49″	61″/9″***	16″	2″	62343	-
310 w/stand*	30	43″	72″/9″***	16″	2″	62441	-
500	45	48″	85″	16″	2″	43850	-
500 w/stand*	30	49″	87″/9″***	16″	2″	40289	-
750	20	72″	56″	16″	2″	40811	-
750 w/stand*	20	73″	67″/11″***	16″	2″	40809	-
1000	45	72″	82″	16″	2″	43852	-
1050	20	72″	75″	16″	2″	40356	-
1050 w/stand*	20	73″	86″/11″***	16″	2″	40359	-
1500	45	72″	112″	16″	2″	43854	-
1600	30	88″	84″	16″	2″	40817	40819
1600 w/stand*	30	89″	96″/11″***	16″	2″	40813	40815
2500	30	95″	105″	16″	2″	40066	40129
2500 w/stand*	30	96″	116″/10″***	16″	2″	40672	40674
2500**	15	91″	108″	16″	2″	43065	43067
3000	30	95″	123″	16″	2″	40170	40172
3000 w/stand*	30	96″	134″/10″***	16″	2″	40797	40799
3000**	15	91″	120″	16″	3″/2″	45141	45242
4500	10	102″	145″	16″	3″/2″	43058	43060
5500	30	119″	148″	16″	3″/2″	40549	40316
6000	15	102″	195″	16″	3″/2″	40931	40933
6000	10	102″	189″	16″	3″/2″	43054	43056
7500	30	141″	149″	16″	3″/2″	40551	40409


Aboveground Plastic Tanks

Cone Bottom Tanks

Polyethylene Cone Bottom Stands

Maintenance free, lightweight Norwesco polyethylene stands offer unequaled corrosion resistance.


Tank Size	A	B	C	D
175 - 30°	-	31 1/2″	8″	43″
300 - 30°	-	32″	8″	49″
310 - 30°	-	31 1/2″	8″	43″
500 - 30°	-	32″	8″	49″
750 - 20°	-	34″	10″	73″
1050 - 20°	-	34″	10″	73″
1600 - 30°	-	46″	10″	89″
2500/3000 - 30°	-	47″	10″	96″



Steel Cone Bottom Stands

Norwesco cone bottom stands are manufactured from structural stetel and offer a full dish for uniform support. An optional top band is available for the 2500/3000 steel stand when additional support is needed.

Tank Size	A	B	C	D	F	Part No.
160 - 45	-	25″	7 1/2″	37″	11″	63932
300/500 - 45	-	32″	8″	49″	11″	63933
1000/1500 - 45	-	42″	10″	73″	11″	63934
2500/3000 - 30	-	36″	11″	96″	11″	60059
4500/6000 - 10	-	20 7/8″	12″	102″	11″	63675
5500 - 30	-	45″	11″	119″	12 1/2″	60358
6000 - 15	-	25″	13″	102″	12 1/8″	62473
7500 - 30	-	49″	11″	140″	10 3/4″	61860
2500/3000 - 30	Optional Top Band Assembly	-	-	-	-	60359



Aboveground Plastic Tanks

High Density Polyethylene Lids

Description	Item Code	Part No.
22" lid and ring with air vent		63679
22" lid, ventless with ring		63863
16" lidand ring with blue snap-in vent	A	63485
16" lid and ring with 3" center thread		63868
16" lid, ventless with ring		60367
16" lid, ventless	B	60365
16" ring only		60012
Ethafoam gasket for 16" non-hinged lid		62941
Blue snap-in vent for 16" lid (63485)		63539
8" lid with blue snap-in vent	C	63480
Blue snap-in vent for 8" lid (63480)		63482
8" lid, ring and air vent (for 22 vertical and loaf tanks)		60032
5" lid with ball check air vent	D	63484
5" lid with 2" FPT (does not include vent cap)		63264
5" lid, hinged (for 52 and 68 gallon flat bottom and 110 low profile tanks)		63673
EPDM gasket for 5" lid, 63264 or 63484		60366
2" MPT vent cap with poly screen		63266
2" MPT vent cap, anti-vortex, without screen		63316
3" MPT vent cap with poly screen		63845
18" lanyard for 8" lid and 16" non-hinged lid (tethers lid to tank)		62531
Stainless steel screw for 8" and 16" rings		60081
Strainer basket for 16" fill-openings (7" depth)		67374
Hinged Lid		
Hinged lid - complete lid assembly - 22"	E	63874
Hinged lid - complete lid assembly - 16"	E	62532
Below Ground Lids		
20" lid for below ground tanks on page 10 (2000 & 2500 gallon)		62408
20" lid for below ground tanks on page 10 (2600 & 2650 gallon)		63672

Aboveground Plastic Tanks

Polypropylene Bulkhead Fittings / EPDM or Viton Gaskets

Our polypropylene fittings come standard with an EPDM gasket. Viton gaskets are available as an options when EPDM may not be suitable for your application. The 2" stainless steel bulkhead fittings comes standard without a gasket.

Description	Hole Size Req	Part No.	Item Code
1/2" Heavy duty double threaded polypropylene fitting	1 7/16"	62834	A
3/4" Double threaded polypropylene fitting	1 7/16"	60401	A
EPDM gasket for 1/2" and 3/4" (62843 and 60401)		60402	
Type B Viton gasket for 1/2" and 3/4" (62834 and 60401)		60360	
3/4" Heavy duty double threaded polypropylene fitting	1 5/8"	62798	A
EPDM gasket 3/4" (62798)		62799	
Type B Viton gasket for 3/4" (62798)		62800	
1" Double threaded polypropylene fitting	2 1/4"	60427	A
1 1/4" Double threaded polypropylene fitting	2 1/4"	60403	A
1 1/4" Anti-vortex polypropylene fitting	2 1/4"	63065	D
EPDM gasket for 1" abd 1 1/4" (60427, 60403, and 63065)		60404	
Type B Viton gasket for 1" and 1 1/4" (60427, 60403, and 63065)		60361	
Anti-vortex adapter for 1 1/4" (60403)		62398	
1 1/2" Double threaded polypropylene fitting	3"	60124	A
Siphon tube, 1 1/2" x 4-15/16" long		63682	
Siphon tube, 1 1/2" x 12" long tube		63279	
1 1/2" Standard duty double threaded polypropylene fitting	2 1/4"	63931	
EPDM gasket for 1 1/2" (63931)		63938	
Type B Viton gasket for 1 1/2' (63931)		63939	
2" Double threaded polypropylene fitting	3"	60405	A
2" Double threaded 316 stainless steel fitting, less gasket	3"	61767	
EPDM gasket for 1 1/2" and 2" (60124, 60405, 63481, and 61767)		60406	
Type B Viton gasket for 1 1/2" and 2" (60124, 60405, 63481, and 61767)		60523	
2" Standard duty double threaded polypropylene fitting	3"	63481	E
(Maximum tank wall thickness = 3/8")			
2" Heavy duty double threaded polypropylene fitting	3 1/4"	63683	B
EPDM gasket for 2" (63683)		60336	
Type B Viton gasket for 2" (63683)		60008	
Siphon tube, 2" short		60335	
Siphon tube, 2" x 12" long		63262	

Continued on next page

Aboveground Plastic Tanks

Polypropylene Bulkhead Fittings / EPDM or Viton Gaskets - Cont'd

Our polypropylene fittings come standard with an EPDM gasket. Viton gaskets are available as an options when EPDM may not be suitable for your application. The 2" stainless steel bulkhead fittings comes standard without a gasket.

Description	Hol Size Req	Part No.	Item Code
2" MPT vent cap with poly screen		63266	
2" MPT vent cap , anti-vortex, without screen		63316	
Anti-vortex adapter for 2" bulkhead fitting		62399	
2" Polypropylene dust plug		60021	
2" Self-aligning double-threaded polypropylene fitting	4 1/2"	63668	
(Designed to install in dome of vertical tank above the liquid level)			
EPDM gasket for 2" self aligning (63668)		60331	
Type B Viton gasket for 2" self aligning (63668)		60351	
3" Double threaded polypropylene fitting	4 1/2"	62299	C
EPDM gasket for 3" (62299)		60331	
Type B Viton gasket for 3" (62299)		60351	
2" Polypropylene reducer for 3"		60330	
Siphon rube, 3" short		60327	
Siphon tube, 3" x 12" long		62363	
3" MPT vent cap with poly screen		63845	
4" Double threaded polypropylene fitting (hex nut as shown in photo C)	5 3/4"	62171	
EPDM gasket for 4" (62171)		62785	
Type B Viton gasket for 4" (62171)		62786	
Siphon tube for 4"		62714	

Aboveground Plastic Tanks

Bolted Fittings

Polypropylene Double Threaded Bolted Fittings / EPDM or Viton Gaskets

Bolted polypropylene fittings are equipped with 316 stainless steel bolts and come standard with EPDM gaskets. Viton gaskets are available as an option for the fittings.

Description	Part No.	Item Code
3/4" Polypropylene bolted fittings with ss bolts and EPDM gaskets	60502	A
1" Polypropylene bolted fitting with ss bolts and EPDM gaskets	60505	A
EPDM gasket for 3/4" and 1"	60498	
Type B Viton gasket for 3/4" and 1"	60355	
1 1/2" Polypropylene bolted fittings with ss bolts and EPDM gaskets	60513	A
2" Polypropylene bolted fitting with ss bolts and EPDM gaskets	60516	A
EPDM gasket for 1 1/2" and 2"	60497	
Type B Viton gasket for 1 1/2" and 2"	60356	
3" Polypropylene bolted fitting with ss bolts and EPDM gaskets	62471	
EPDM gasket for 3"	62048	
Type B Viton gasket for 3"	60602	

Stainless Steel Single Threaded Bolted Fittings

Description	Part No.
2" 316 Stainless steel single threaded bolted fitting less gasket	62847
EPDM gasket for 1 1/4", 1 1/2", and 2" (1 required)	63206
Type B Viton gasket for 1 1/4", 1 1/2", and 2" (1 required)	63225
Cross-linked polyethylene gasket for 2" (1 required)	62848
3" 316 Stainless steel single threaded bolted fitting, anti-vortex, less gasket	63233
EPDM gasket for 3" (1 required)	63223
Type B Viton gasket for 3" (1 required)	63226
Cross-linked polyethylene gasket for 3" (1 required)	63043



A


Aboveground Plastic Tanks

Bolted Fittings


Stainless Steel Double Threaded Bolted Fittings

Bolts are threaded into the back plate of the fitting so there are no welds or bolt holes tha can be potential points of leakage. These fittings come standard without a gasket and require a single gasket that is installed on the inside of the tank. Avavilable gaskets are cross-linkedin poylethylene, EPDM, or Viton.

Description	Part No.	Item Code
1/2" 316 Stainless steel double threaded bolted fitting less gasket	63216	B
3/4" 316 Stainless steel double threaded bolted fitting less gasket	63035	B
1" 316 Stainless steel double threaded bolted fitting less gasket	62948	B
EPDM gasket for 1/2", 3/4", and 1" (1 required)	63205	
Type B Viton gasket for 1/2", 3/4", and 1" (1 required)	63224	
Cross-linked polyethylene gasket for 1/2", 3/4", and 1" (1 required)	62950	
1 1/4" 316 Stainless steel double threaded bolted fitting less gasket	63036	B
Cross-linked polyethylene gasket for 1 1/4" (1 required)	63041	
1 1/2" 316 Stainless steel double threaded bolted fitting less gasket	63037	B
EPDM gasket for 1 1/4" and 1 1/2" (1 required)	63426	
Cross-linked polyethylene gasket for 1 1/2" (1 required)	63042	
2" 316 Stainless steel double threaded bolted fitting less gasket	63038	B
EPDM gasket for 2" (1 required)	63206	
Type B Viton gasket for 1 1/4", 1 1/2", and 2" (1 required)	63225	
Cross-linked polyethylene gasket for 2" (1 required)	62848	
3" 316 Stainless steel double threaded botled fitting less gasket	63039	C
EPDM gasket for 3" (1 required)	63223	
Type B Viton gasket for 3" (1 required)	63226	
Cross-linked polyethylene gasket for 3" (1 required)	63043	
4" 316 Stainless steel 8-bolt double threaded bolted fitting with gasket	63688	
EPDM gasket for 4" (1 required)	63690	
Viton gasket for 4" (1 required)	63691	
Cross-linked polyethylene gasket for 4" (1 required)	63689	



B



C

Belowground Plastic Tanks

Septic Tanks & Accessories

Norwesco Low Profile Septic Tanks are molded in one piece, requiring no additional assembly, reducing installation time and effort.

- Rotationally molded rugged, one-piece tank with no seams to leak.
- No assembly required, reducing installation time and effort.
- No special backfill or water filling required during installation.
- May be pumped dry during pump-outs.
- May be installed with 6" to 36" of cover.
- Suitable for use as a septic tank or pump tanks and may also be used non-potable water.
- Access openings and lids accept NORWESCO manhole extension, double-wall corrugated pipe and ribbed PVC pipe.
- Tanks are available with PVC tees and gaskets supplied loose or with isntalled PVC tees and septic adapters.

Low Profile Septic Tanks

Gallon Capacity	Length	Width	Overall Height	Manhole Diameter	Compartment Availability
500	97"	48"	42"	2-20" (63672)	Single or Double
750	92"	60"	51"	2-20" (63672)	Single or Double
1000	127"	60"	51"	2-20" (63672)	Single or Double
1250	157"	60"	51"	2-20" (63672)	Single or Double
1500	157"	69"	51"	2-20" (63672)	Single or Double

Low Profile Septic Tank Accessories

Description	Part No.
Manhole extension (6"H x 20"D)*	63832
Manhole extension (15"H x 20"D)*	63833
Manhole extension (24"H x 20"D)*	63834
Lid riser (36"H x 6"D)*	63830
Lid riser, offset (23"H x 12"D)*	63831
Stainless steel self-tapping screw (#14 x 1 3/4) for extensions and risers (8 required)	63870
Ethafoam gasket for extensions or risers	62942
20" Septic tank lid without gasket	63672
Self-adhesive rubber gasket for 20" lid (63672)	63839
Stainless steel self-tapping screw, #14 x 1 1/4, for 20" lid (63672) (6 required)	62406

Replacement Plumbing Accessories

Description	Part No.
4" PVC inlet/outlet tee (24" long) (2 per tank)	63491
4" inlet/outlet gasket (2 per tank)	63490
Septic Adapter Schedule 40 with nut & EPDM gasket (2 per tank)	63152

Belowground Plastic Tanks

Polyethylene Septic Tanks

Norwesco septic tanks are for below ground use only. Using the tanks above ground may result in deformation of the tank. It is far more cost-effective to utilize one of Norwesco's above ground tanks that are specifically designed for above ground use and applications. These tanks cannot be used as pump tanks and must be kept full at all times.

Gallon Capacity	Length	Width	OverallHeight	Height to Inlet	Height to Outlet	Manhole Diameter	Compartment Availability
500	101	51	47	36	3	1-20" (62408)	Single
750	96	52	62	51	48	1-20" (62408)	Single
750	96	48	63	52	49	2-20" (62408)	Single
750	100	52	59	49	46	2-20" (62408)	Single
750	100	52	59	49	46	2-20" (62408)	Double
1000	101	52	71	59	56	1-20" (62408)	Single
1000	102	60	63	51	48	2-20" (62408)	Single or Double
1250	116	55	70	59	56	2-20" (62408)	Single or Double
1500	135	55	70	59	56	2-20" (62408)	Single or Double

The Bruiser

The Bruiser offers the same features as our standar septic tanks but it may be used as a septic tank as well as a holding tanks, pump chamber, or a potable water tank (single compartment only).

- No special backfill is needed. Native soil may be used.
- Use where delivery of special backfill mictures and water is next to impossible.
- No need to fill with water during initial installation.
- Pre-plumbed according to state code.
- Accepts 4" effluent filters.
- Suitable for use as a potable water tank (single compartment only).

Gallon Capacity	Length	Width	OverallHeight	Height to Inlet	Height to Outlet	Manhole Diameter	Compartment Availability
500	101	51	47	36	3	1-20" (62408)	Single
750	96	52	62	51	48	1-20" (62408)	Single
750	96	48	63	52	49	2-20" (62408)	Single
750	100	52	59	49	46	2-20" (62408)	Single

Belowground Spherical Pump Tanks

Our 200, 300, and 500 gallon spheres are designed to be used aas a holding tank or pump tank. Unlike the ribbed septic tanks, these tanks may remain in the ground when empty. These tanks are furnished with manhole covers and include a molded-in elevated pump stand on the bottom of the tank.

Gallon Capacity	Diameter	Overall Height	Height to Inlet	Height to Outlet	Manhole Diameter	Part No.
200 Sphere	47	56	-	-	1-20" (62408)	43745
300 Sphere	54	54	44	42	1-20" (62408)	41319
500 Sphere	64	67	56	53	1-20" (62408)	40785

Belowground Plastic Tanks

Belowground Holding Tanks

Norwesco holding tanks are the largest capacity below ground storage tanks made today. Typically used to store water - both potable and non-potable - it can also be used as a large capacity septic tank. The end ribs will accept fittings up to 4" in size. Integral columns in the tank give it excellent structural strength.



Gallon Capacity	Length	Width	Overall Height	Manhole Diameter	Part No
2000	126	98	53	1-20" (62408)	42559
2500	158	98	53	1-20" (62408)	42119
2600	155	98	51	1-20" (63672)	43770
2650	155	98	81	1-20" (63672)	43771

Belowground Cistern Tanks

Our below-ground cisterns feature the same rugged ribbed design found in our septic tanks and are lightweight for ease of transport and installation.



Gallon Capacity	Length	Width	Overall Height	Manhole Diameter	Part No
250 Cistern Sphere	-	47 Dia	56	1-20" (62408)	43746
325 Cistern Sphere	-	54 Dia	54	1-20" (62408)	41321
550 Cistern Sphere	-	64 Dia	67	1-20" (62408)	40856
600 Cistern	101	51	47	1-20" (62408)	41328
1200 Cistern	102	60	63	2-20" (62408)	41329
1400 Cistern	116	55	70	2-20" (62408)	41893
1700 Cistern	135	55	70	2-20" (62408)	41330

Belowground Plastic Tanks

Belowground Ribbed Septic, Cistern, and Bruiser Accessories

Description	Part No.
Manhole extension (6" H x 20"D)	63514
Manhole extension (15" H x 20"D)	62397
Manhole extension (24" H x 20"D)	62396
Lid and riser combination (12" D x 25" H riser pipe)	62395
20" Septic/cistern tank lid with gasket	62408
SDR35 Sanitary Tee & Gasket Kit (2 each)	61762
Schedule 40 Sanitary Tee & Gasket Kit (2 each)	61763
SDR35/Schedule 40 Gasket Kit (2 each)	61765
Stainless steel self-tapping screw, #14 x 1 1/4", for 20" lid 62408 (4 required)	62406
Stainless steel self-tapping screw, childproof (required for tanks installed in NM & WI)	63522
Tamper proof screw kits for tanks installed in NM & WI (Includes 8 stinaless steel self-tapping childproof screws and 1 square recess bit)	63564
Ethafoam gasket for 20" lid	62942
Septic Adapter SDR35 with nut and EPDM gasket	63151
Septic Adapter Schedule 40 with nut and EPDM gasket	63152
EPDM gasket for septic adapter	63153

Commercial Grade Plastic Tanks

Vertical Bulk Storage Tanks

Vertical - Dome Top

Part No.	Capacity	Specific Gravity	Weight	Dimensions (diameter x height)	Lid (in)	Fitting
VT0010-12	10 gallon	2.0	9	12 x 25	8"	3/4"
VT0020-16	20 gallon	2.0	13	16 x 28	8"	3/4"
VT0025-18	25 gallon	2.0	12	18 x 30	5"	3/4"
VT0040-18	40 gallon	2.0	17	18 x 43	5"	3/4"
VT0055-20	55 gallon	2.0	22	20 x 47	5"	1"
VT0065-23	65 gallon	2.0	25	23 x 42	5"	1"
VT0110-32	110 gallon	2.0	40	32 x 41	5"	2" top
VT0135-23	135 gallon	2.0	47	23 x 82	16"	1"
VT0300-42	300 gallon	2.0	73	42 x 55	8"	2"
VT0405-52	405 gallon	2.0	90	52 x 48	8"	2"
VT0425-42	425 gallon	2.0	101	42 x 75	8"	2"
VT0505-46	505 gallon	2.0	118	46 x 80	16"	2"
VT0550-52	550 gallon	2.0	116	52 x 66	8"	2"
VT0600-46	600 gallon	2.0	130	46 x 91	16"	2"
VT0625-64	625 gallon	2.0	100	64 x 50	8"	2"
VT0800-46	800 gallon	1.7	175	46 x 118	16"	2"
VT0900-46	900 gallon	1.7	220	46 x 132	16"	2"
VT1000-64	1000 gallon	1.7	250	64 x 81	16"	2"
VT1050-86	1050 gallon	1.7	190	86 x 54	16"	2"
VT1200-64	1200 gallon	1.7	275	64 x 97	16"	2"
VT1350-86	1350 gallon	1.7	228	86 x 65	16"	2"
VT1500-64	1500 gallon	1.7	335	64 x 115	16"	2"
VT1500-86	1500 gallon	1.7	250	86 x 69	16"	2"
VT1525-64	1525 gallon	1.7	350	64 x 122	16"	2"
VT1650-86	1650 gallon	1.7	276	86 x 74	16"	2"
VT2000-64	2000 gallon	1.7	465	64 x 156	16"	2"
VT2000-90	2000 gallon	1.7	375	90 x 84	16"	2"
VT2050-86	2050 gallon	1.7	402	86 x 93	16"	2"
VT2150-102	2150 gallon	1.7	417	102 x 71	16"	2"
VT2500-90	2500 gallon	1.7	420	90 x 103	16"	2"
VT3000-90	3000 gallon	1.7	550	90 x 120	16"	2"
VT3100-102	3100 gallon	1.7	550	102 x 103	16"	2"
VT3400-102	3400 gallon	1.7	585	102 x 107	16"	2"

Commercial Grade Plastic Tanks

Vertical Bulk Storage Tanks

Vertical - Dome Top (Cont'd)

Part No.	Capacity	Specific Gravity	Weight	Dimensions (diameter x height)	Lid (in)	Fitting
VT4000-96	4000 gallon	1.7	900	96 x 140	16"	2"
VT4200-96	4200 gallon	1.7	950	96 x 148	16"	2"
VT5000-102	5000 gallon	1.7	1302	102 x 156	16"	3"
VTT5150-102	5150 gallon	1.7	1350	102 x 161	16"	3"
VT6250-102	6250 gallon	1.7	1550	102 x 194	16"	3"
VT6500-120	6500 gallon	1.7	1502	120 x 152	16"	3"
VT7000-142	7000 gallon	1.7	1750	142 x 125	16"	3"
VT7800-120	7800 gallon	1.7	1900	120 x 176	16"	3"
VT8000-120	8000 gallon	1.7	1930	120 x 180	16"	3"
VT9150-120	9150 gallon	1.7	2200	120 x 203	16"	3"
VT9500-120	9500 gallon	1.7	2352	120 x 213	16"	3"
VT10500-2500	10500 gallon	1.6	2500	142 x 177	16"	3"
VT10500-2800	10500 gallon	1.8	2800	142 x 177	16"	3"
VT12500-142	12500 gallon	1.7	3402	142 x 208	16"	3"



Commercial Grade Plastic Tanks

Vertical Bulk Storage Tanks

Vertical - Flat Top

These vertical tanks feature additional flats for fitting installation or mounting.



Part No.	Capacity	Specific Gravity	Weight	Dimensions (diameter x height)	Lid (in)	Fitting
VT0055-23	55 gallon	2.0	26	23 x 38	8″	1″
VT0075-23	75 gallon	2.0	28	23 x 50	7″	1″
VT0100-23	100 gallon	2.0	36	23 x 64	8″	1″
VT0100-28	100 gallon	2.0	36	28 x 45	7″	1″
VT0105-23	105 gallon	2.0	38	23 x 65	7″	1″
VT0130-32	130 gallon	2.0	47	32 x 46	8″	1″
VT0135-28	135 gallon	2.0	45	28 x 59	8″	1″
VT0145-36	145 gallon	2.0	52	36 x 40	8″	1″
VT0160-28	160 gallon	2.0	56	28 x 68	8″	1″
VT0175-31	175 gallon	2.0	54	31 x 61	8″	1 1/2″
VT0180-40	180 gallon	2.0	48	40 x 45	5″	2″ top (molded in)
VT0200-36	200 gallon	2.0	58	36 x 53	8″	1 1/2″
VT0210-40	210 gallon	2.0	56	40 x 49	5″	2″ top (molded in)
VT0225-31	225 gallon	2.0	65	31 x 76	8″	1 1/2″
VT0250-36	250 gallon	2.0	76	36 x 62	8″	1 1/2″
VT0265-31	265 gallon	2.0	74	31 x 88	8″	1 1/2″
VT0295-42	295 gallon	2.0	74	42 x 55	16″	2″
VT0300-35	300 gallon	2.0	86	35 x 81	8″	2″
VT0325-36	325 gallon	2.0	92	36 x 81	8″	2″
VT0420-42	420 gallon	2.0	102	42 x 75	16″	2″
VT0500-46	500 gallon	2.0	118	46 x 77	8″	2″
VT0850-54	850 gallon	1.7	182	54 x 94	8″	2″

Commercial Grade Plastic Tanks

Free-Standing Horizontal Bulk Storage Tanks

Free Standing Tanks are selected when transportable (non DOT regulated) containment is required for infoor or outdoor applications. Tanks are equipped with molded-in legs to support the tank and band locators for tie- down. Tanks are manufactured from medium- or high-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Free Standing Horizontal Without Sump

Part No.	Capacity		Weight	Dimensions	Lid (in)	Fitting (in)
FS0035-18	35 gallon		16	18 x 34	5	1
FS0065-24	65 gallon		33	24 x 39	5	1
FS0070-24	70 gallon	stackable (3 high)	35	24 x 39	5	1
FS0125-32	125 gallon		52	32 x 40	8	1
FS0165-32	165 gallon		70	32 x 54	8	1
FS0225-38	225 gallon		85	38 x 52	8	2
FS0325-38	325 gallon		106	38 x 72	12	2
FS0335-44	335 gallon		116	44 x 56	16	2
FS0510-57	510 gallon	Elliptical	162	57 x 80 x 39	16	2
FS0535-48	535 gallon		160	48 x 78	16	2
FS0735-48	735 gallon (hoops req.)		250	48 x 103	16	2
FS0925-DW	925 gallon (hoops req.)		290	62 x 81	16	2
FS1005-48	1005 gallon (hoops req.)		340	48 x 130	16	2
FS1010-48	1010 gallon (hoops & skid req.)		340	48 x 130	16	2
FS1035-78	1035 gallon (hoops req.)	Elliptical	290	78 x 90 x 52	16	2
FS1065-56W	1065 gallon (hoops req.)		340	56 x 105	16	2
FS1300-DW	1300 gallon (hoops req.)		425	62 x 114	16	2
FS1750-62W	1750 gallon (hoops req.)		616	62 x 147	16	2
FS1800-2W	1800 gallon (hoops req.)	multi tanks (2)	580	62 x 149	16	2
FS2350-88	2350 gallon (hoops req.)	Elliptical	920	88 x 146 x 63	16	2
FS2600-2W	2600 gallon (hoops req.)	multi tanks (2)	850	62 x 212	16	2
FS2750-88	2750 gallon (hoops req.)	Elliptical	1150	88 x 146 x 70	16	2
FS3200-2S	3200 gallon (hoops req.)	multi tanks (2) / Elliptical	1100	88 x 172 x 74	16	2
FS3250-88	3250 gallon (hoops & skid req.)	Elliptical	1208	88 x 146 x 79	16	2

Commercial Grade Plastic Tanks

Free-Standing Horizontal With Sump

Part No.	Capacity		Weight	Dimensions	Lid (in)	Fitting (in)
FM0015-14S	15 gallon		11	14 x 30	5	
FM0025-16S	25 gallon		15	16 x 34	5	
FM0925-DS	925 gallon (hoops req)		290	62 x 81	16	2
FM1065-56S	1065 gallon (hoops req)		340	56 x 105	16	2
FM1300-DS	1300 gallon (hoops req)		425	62 x 114	16	2
FM1610-78S	1610 gallon (hoops req)	center or end drain/ elliptical	530	78 x 139 x 58	16	2
FM1750-62S	1750 gallon (hoops req)		616	62 x 147	16	2
FM1800-2S	1800 gallon (hoops req)	multi tanks (2)	580	62 x 149	16	2
FM2350-88S	2350 gallon (hoops req)	center or end drain/ elliptical	920	88 x 146 x 63	16	2
FM2600-2S	2600 gallon (hoops req)	multi tanks (2)	850	62 x 212	16	2
FM2750-88S	2750 gallon (hoops req)	center or end drain/ elliptical	1150	88 x 146 x 70	16	2
FM3250-88S	3250 gallon (hoops req)	center or end drain/ elliptical	1208	88 x 146 x 79	16	2



Commercial Grade Plastic Tanks

Hoops, Baffles, & Skids

Part No.	Capacity	Weight	Dimensions
FS048-HP	735 gal hoops	set of 3	1.315 OD
FS062-HP-925	925 gal hoops	set of 2	1.66 OD
FS062-HP-1300	1300 gal hoops	set of 3	1.66 OD
FS062-HP-1750	1750 gal hoops	set of 4	1.66 OD
FS062-HP-1800C	1800 gal hoops	set of 4	1.66 OD
FS062-HP-2600C	2600 gal hoops	set of 6	1.66 OD
FS0510-HP	510 gal hoops	set of 3	1.315 OD
FS1005-HP	1005 gal hoops	set of 4	1.315 OD
FS1010-HP	1010 gal hoops	set of 4	1.315 OD
FS1035-HP	1035 gal hoops	set of 3	1.66 OD
FS1065-HP	1065 gal hoops	set of 3	1.315 OD
FS1065-BAF	1065 gal baffles	38	
FS1610-HP	1610 gal hoops	set of 4	1.66 OD
FS2350-HP	2350 gal hoops	set of 4	1.90 OD
FS2750-HP	2750 gal hoops	set of 4	1.90 OD
FS3200-HP	3200 gal hoops	set of 4	1.66 OD
FS3250-HP	3250 gal hoops	set of 4	1.90 OD
FS3250-LAD	3250 ladder	46	16 x 78
FS0925-SK	925 gal skis	280	61 x 64
FS1010-SK	1010 gal skid	409	53 x 115
FM1065-SKS	1065 gal skid w/ sump	280	61 x 78
FS1065-SKW	1065 gal skid w/o sump	200	59 x 100
FS1300-SK	1300 gal skid	450	64 x 104
FM1610-SKC	1610 gal skid w/c sump	490	83 x 107
FM1610-SKE	1610 gal skid w/e sump	490	83 x 112
FS1750-SK	1750 gal skid	604	64 x 138
FM1800-SKS	1800 gal skid w/ sump	580	64 x 125
FS1800-SKW	1800 gal skid w/o sump	382	64 x 125
FM2350/3250-SKC	2350/2750/3250 gal skid w/c sump	1060	88 x 141
FM2350/3250-SKE	2350/2750/3250 gal skid w/e sump	1060	88 x 141
FS2350/3250-SK	2350/2750/3250 gal skid	1078	88 x 141
FS2600-SK	2600 gal skid	900	64 x 201
FS3200-SK	3200 gal skid	1163	90 x 168

Commercial Grade Plastic Tanks

Free-Standing Horizontal Leg Tanks/Hoops, Skids & Bands

Powder Coated Steel Bands With J-Bolt

Heavy gauge steel bands available for 35 through 535-gallon tanks. Silver powder coated finish on all bands except 35 and 65-gallon tanks which are stainless steel. Bands feature reinforced holes for J-Bolts which allow additional mounting hole flexibility.

Part No.	Capacity	Weight	Bands
FS0035-SB	35 gallon kit silver	18 ga	2 x 45
FS0065-SB	65 gallon kit silver	18 ga	2 x 61
FS125/165-SBOJ	125/165 gallon kit silver	14 ga	3 x 80
FS225/325-SBPJ	225/325 gallon kit silver	14 ga	3 x 95
FS0335-SBPJ	335 gallon kit silver	14 ga	3 x 110
FS0535-SBPJ	535 gallon kit silver	14 ga	3 x 120

Powder Coated Steel Bands With Formed Feet

Heavy gauge steel bands available for 35 through 535-gallon tanks. Silver powder coated finish on all bands. Bands feature a formed foot for securely fastening tank to platform surface. Formed foot provides a more rigid connection for tank.

Part No.	Capacity	Weight	Bands
FS0035-SBPF	35 gallon kit silver	8	2 x 47.5
FS0065-SBPF	65 gallon kit silver	12	2 x 67
FS125/165-SBPF	125/165 gallon kit silver	16	2.5 x 84.5
FS225/325-SBPF	225/325 gallon kit silver	19	2.5 x 99.5
FS0335-SBPF	335 gallon kit silver	34	2.75 x 116.5
FS0535-SBPF	535 gallon kit silver	36	2.75 x 125

Baffles

Ace Roto-Mold has developed a unique baffle system that is easy to install and clean. These baffles help to reduce fluid sloshing. Baffle systems come standard in some tanks and offered as an option in others.

Optional	Standard
FS1065-56W	FM1610-78S
FM1065-56S	FM1750-62W
	FS1750-62S
	FS2350-88
	FM2350-88S
	FS2750-88
	FM2750-88S
	FS3250-88
	FM3250-88S

Commercial Grade Plastic Tanks

Elliptical Tanks

Elliptical tanks can be selected for stationary or transportable (non DOT) regulated applications both indoors and outdoors. The elliptical tank lowers the center of gravity to enhance stability and visibility. The tanks feature a standard 2-1/2" collection sump on the bottom for full drain out. An 8-1/2" deep sump option is available on five sizes. Sump is located directly under the lid on standard tanks, but a center sump option is available on tanks from 500-1200 gallons. These tanks require the bottom to be fully supported with a cradle for use. The tanks are manufactured from medium-density polyethylene with U.V. stabilizers and are designed for containment of liquids up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions (W x L x H)	Lid (in)	Fitting (in)
HE0200-41	200 gallon	82	41 x 66 x 26	8	3/4 & 1-1/4
HE0300-48	300 gallon	112	48 x 70 x 30	8	3/4 & 1-1/4
HE0400-57	400 gallon	127	57 x 70 x 36	8	3/4 & 1-1/4
HE0500-57	500 gallon	163	57 x 82 x 36	8	3/4 & 1-1/4
HED0500-57	500 gallon deep (8.5") sump	163	57 x 82 x 36	8	3/4 & 1-1/4
HE0750-69	750 gallon	220	69 x 89 x 42	16	1-1/4 & 2
HED0750-69	750 gallon deep (8.5") sump	220	69 x 89 x 42	16	1-1/4 & 2
HE0850-69	850 gallon	246	69 x 89 x 46	16	1-1/4 & 2
HED0850-69	850 gallon deep (8.5") sump	246	69 x 89 x 46	16	1-1/4 & 2
HE1000-78	1000 gallon	285	78 x 90 x 49	16	1-1/4 & 2
HED1000-78	1000 gallon deep (8.5") sump	285	78 x 90 x 49	16	1-1/4 & 2
HE1250-78	1250 gallon	400	78 x 92 x 60	16	1-1/4 & 2
HED1250-78	1250 gallon deep (8.5") sump	400	78 x 92 x 60	16	1-1/4 & 2
HE1600-78	1600 gallon	439	78 x 138 x 49	16	2
HED1600-78	1600 gallon deep (6") sump	439	78 x 138 x 49	16	2

Cradles for Elliptical Tanks

Part No.	Capacity	Weight	Bands (in)
HE0200-C	200 gallon	140	3 x 61
HE0300-C	300 gallon	155	3 x 74
HE0400-C	400 gallon	190	4 x 88
HE0500-C	500 gallon	202	4 x 88
HE0750-C	750 gallon	405	4 x 91
HE0850-C	850 gallon	408	4 x 99
HE1000-C	1000 gallon	515	4 x 105
HE1250-C	1250 gallon	520	4 x 126
HE1600-C	1600 gallon	578	3.5 x 124

Commercial Grade Plastic Tanks

Round Horizontal Bulk Storage Tanks

Round horizontal tanks are selected when transportable (non DOT) regulated containment is required for indoor or outdoor applications. Tanks require skids and bands to support the round bottom. All tanks are equipped with drain out sumps. Tanks are manufactured from medium-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions (W x L x H)	Lid (in)	Fitting (in)
HE0200-41	200 gallon	82	41 x 66 x 26	8	3/4 & 1-1/4
HE0300-48	300 gallon	112	48 x 70 x 30	8	3/4 & 1-1/4
HE0400-57	400 gallon	127	57 x 70 x 36	8	3/4 & 1-1/4
HE0500-57	500 gallon	163	57 x 82 x 36	8	3/4 & 1-1/4
HED0500-57	500 gallon deep (8.5") sump	163	57 x 82 x 36	8	3/4 & 1-1/4
HE0750-69	750 gallon	220	69 x 89 x 42	16	1-1/4 & 2
HED0750-69	750 gallon deep (8.5") sump	220	69 x 89 x 42	16	1-1/4 & 2
HE0850-69	850 gallon	246	69 x 89 x 46	16	1-1/4 & 2
HED0850-69	850 gallon deep (8.5") sump	246	69 x 89 x 46	16	1-1/4 & 2
HE1000-78	1000 gallon	285	78 x 90 x 49	16	1-1/4 & 2
HED1000-78	1000 gallon deep (8.5") sump	285	78 x 90 x 49	16	1-1/4 & 2
HE1250-78	1250 gallon	400	78 x 92 x 60	16	1-1/4 & 2
HED1250-78	1250 gallon deep (8.5") sump	400	78 x 92 x 60	16	1-1/4 & 2
HE1600-78	1600 gallon	439	78 x 138 x 49	16	2
HED1600-78	1600 gallon deep (6") sump	439	78 x 138 x 49	16	2

Cradles for Horizontal Tanks

Part No.	Capacity	Weight	Bands
HZ0025-C	25 gallon	20	1.5" x 50"
HZ0055-C	55 gallon	24	2" x 50.5"
HZ0075-C	75 gallon	36	2" x 51.5"
HZ0095-C	95 gallon	38	2" x 51.5"
HZ0100-C	100 gallon	40	1.75" x 39.5"
HZ0110-C	110 gallon	40	2.75" x 60"
HZ0153-C	150 gallon x 30	57	2.75" x 55"
HZ0150-C	150 gallon x 32	56	2.75" x 56"
HZ0232-C	200 gallon x 32	110	2.75" x 57"
HZ0238-C	200 gallon x 38	85	2.75" x 65"
HZ0300-C	300 gallon	145	2.75" x 69.5"
HZ0500-C	500 gallon	170	2.75" x 86.5"

Commercial Grade Plastic Tanks

Cone Bottom Bulk Storage Tanks

Cone bottom tanks are selected when a more complete drain out of stored chemical is required in indoor or outdoor installations. Tanks require stands to support the conical bottoms. Tanks are manufactured from medium- or high-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Specific Gravity	Weight	Tank Dimensions (diameter x height)	Overall Height (incl. stand)	Lid (in)	Fitting (in)
CB0300-42	300 gallon - 45 deg	2	100	42 x 67	79″	16	2
CB0800-86	800 gallon - 15 deg	1.7	182	86 x 48	58″	16	2
CB1000-64	1000 gallon - 45 deg	1.7	250	64 x 98	112″	16	2
CB1000-90	1000 gallon - 15 deg	1.7	212	90 x 54	64″	16	2
CB1200-90	1200 gallon - 15 deg	1.7	240	90 x 62	74″	16	2
CB1300-90	1300 gallon - 15 deg	1.7	262	90 x 65	75″	16	2
CB1490-64	1490 gallon - 45 deg	1.7	340	64 x 132	146″	16	2
CB1600-90	1600 gallon - 30 deg	1.7	284	90 x 85	94″	16	2
CB1700-86	1700 gallon - 15 deg	1.7	284	86 x 85	96″	16	2
CB2500-90	2500 gallon - 15 deg	1.7	435	90 x 111	122″	16	2
CB2600-90	2600 gallon - 30 deg	1.7	500	90 x 123	132″	16	2
CB2600-86	2600 gallon - 45 deg	1.7	500	86 x 146	158″	16	2
CB3000-90	3000 gallon - 15 deg	1.7	550	90 x 128	138″	16	2
CB3000-96	3000 gallon - 30 deg	1.7	552	96 x 125	137″	16	2
CB4600-102	4600 gallon - 15 deg	1.7	1200	102 x 155	166″	16	2
CB4900-102	4900 gallon - 15 deg	1.7	1300	122 x 159	170″	16	2
CB6900-122	6900 gallon - 15 deg	1.7	1700	122 x 168	178″	16	2
CB8250-122	8250 gallon - 15 deg	1.7	2100	122 x 195	206″	16	2

Cone Bottom Stands

Part No.	Capacity	Weight	Clearance (tank to ground)
CB023-15ST	55 or 100 gal - 15 deg	37	13″
CB036-15ST	145, 200, 250, or 325 gal - 15 deg	84	12″
CB036-45ST	150 gal - 45 deg	63	12″
CB042-45ST	200, 300 or 350 gal - 45 deg	82	11″
CBFD042-45ST	240 gal full drain - 45 deg	82	10″
CB052-45ST	345 or 500 gal - 45 deg	174	13″
CB064-45ST	1000 or 1490 gal - 45 deg	320	14″
CB086-15ST	800 or 1700 gal - 15 deg	360	11″
CB086-45ST	2600 gal - 45 deg	580	12″
CB090-15ST	850, 1000, 1150, 1200, 1300, 2450, 2500, or 3000 gal - 15 deg	380	11″
CB090-30ST	1550, 1600, 2550, or 2600 gal - 30 deg	640	9″
CB096-30ST	3000 gal - 30 deg	553	12″
CB102-15ST	4600 or 4900 gal - 15 deg	640	11″
CB122-15ST	6900 or 8250 gal - 15 deg	1020	10″

Commercial Grade Plastic Tanks

Cone Bottom - Flat Top

These Cone Bottom Tanks feature additional flats for fitting installation or mounting.

Part No.	Capacity	Specific Gravity	Weight	Tank Dimensions (diameter x height)	Overall Height (incl. stand)	Lid	Fitting
CB0055-23	55 gallon - 15 deg	2.0	26	23 x 36	52″	8″	1-1/2″
CB0100-23	100 gallon - 15 deg	2.0	36	23 x 62	78″	8″	1-1/2″
CB0145-36	145 gallon - 15 deg	2.0	52	36 x 43	56″	8″	2″
CB0150-36	150 gallon - 45 deg	2.0	61	36 x 51	63″	12″	2″
CB0200-36	200 gallon - 15 deg	2.0	58	36 x 55	68″	8″	2″
CB0200-42	200 gallon - 45 deg	2.0	75	42 x 55	66″	12″	2″
CBFD240-42	240 gal full drain - 45 deg	1.7	77	42 x 59	69″	12″	2″
CB0250-36	250 gallon - 15 deg	2.0	76	36 x 69	80″	8″	2″
CB0325-36	325 gallon - 15 deg	2.0	92	36 x 84	97″	8″	2″
CB0345-52	345 gallon - 45 deg	2.0	100	52 x 58	70″	12″	2″
CB0350-42	350 gallon - 45 deg	2.0	118	42 x 81	93″	12″	2″
CB0500-52	500 gallon - 45 deg	2.0	130	52 x 81	92″	12″	2″
CB0850-90	850 gallon - 15 deg	1.7	212	90 x 56	67″	16″	2″
CB1150-90	1150 gallon - 15 deg	1.7	242	90 x 67	78″	16″	2″
CB1550-90	1550 gallon - 30 deg	1.7	286	90 x 88	97″	16″	2″
CB2450-90	2450 gallon - 15 deg	1.7	437	90 x 114	125″	16″	2″
CB2550-90	2550 gallon - 30 deg	1.7	502	90 x 126	134″	16″	2″

Cone Bottom - Flat Top

Blow molded inductor tank sets are designed for indoor or outdoor stationary applications. Anchor kits are available for transportable (non DOT regulated) applications. Four blow molded polyethylene legs are included that attach directly to the tank with stinaless steel hardware. Tanks feature full drain conical bottoms and outlet for complete drainage. Tank walls are translucent for level viewing and equipped with gallon/litre indicators. Tanks are manufactured from high-density polyethylene with U.V. inhibitors and are designed for the containment of liquids of up to 1.7 specific gravity.

Part No.	Capacity	Weight	Case Dimensions	Lid	Fitting
IBFD35-SET	35 gallon full drain	41	25 x 25 x 43	12″	2″ FPT
IBFD60-SET	60 gallon full drain	47	25 x 25 x 55	12″	2″ FPT

Commercial Grade Plastic Tanks

Inductor Tanks

Inductor tanks are selected as supply tanks for indoor or outdoor applications and feature conical bottoms to facilitate liquid drain out. Tanks feature a bulkhead fitting for supply line connection. Full drain tanks are available with molded in threaded outlet for complete drainage. Tanks require stands to support the conical bottoms. Tanks are manufactured from medium-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid (in)	Fitting
IN0015-19	15 gallon	10	19 x 24	12	2" FPT
INFD15-19	15 gallon full drain	10	19 x 27	12	1 1/2" FPT BOSS
IN0015-19SM	15 gallon side mount	8	19 x 24	12	2" FPT
IN0030-24	30 gallon	15	24 x 30	12	2" FPT
INFD30-24	30 gallon full drain	15	24 x 33	12	1 1/2" FPT BOSS
IN0040-30	40 gallon full drain	26	30 x 34	12	2" MPT BOSS
IN0060-24	60 gallon x 24	22	24 x 42	12	2" FPT
INFD60-24	60 gallon x 24 full drain	22	24 x 46	12	1 1/2" FPT BOSS
INFD60-30	60 gallon x 30 full drain	26	30 x 38	16	2" MPT BOSS
IN0085-30	85 gallon	37	30 x 43	12	2" FPT
INFD85-30	85 gallon full drain	37	30 x 48	12	2" FPT BOSS
IN0110-30	110 gallon	44	30 x 51	12	2" FPT
INFD110-30	110 gallon full drain	44	30 x 56	12	2" FPT BOSS

Cradles for Horizontal Tanks

Part No.	Capacity	Weight
IN15-ST	15 gallon	15
INFD15-ST	15 gallon (4" taller for full-drain tanks)	16
IN30/60-ST	30 or 60 gallon (for 24" dia. tanks)	18
INFD30/60-ST	30 or 60 gallon (4" taller for full-drain tanks)	19
IN40/85-ST	40, 60, 85, or 110 gallon (for 30" dia. Tanks)	40
IN40-ST	40 gallon (UPS)	40

Commercial Grade Plastic Tanks

Batch Tanks

These batch tanks are designed for indoor applications. The tanks support many features including vertical, open top vertical, cone bottom as well as open top cone bottom options. All tanks feature 8" lids and one standard fitting. A hinged lid option is also available on the open top styles. Both polyethylene and metal stands designed for all styles make these tanks very versatile. Tanks are manufactured from medium-density polyethylene with U.V. inhibitors and are designed for the containment of liquids up to 2.0 specific gravity. Tank walls are translucent for level viewing and equipped with liter and gallon indicators.

Vertical - Open Top

Part No	Capacity		Weight	Dimensions	Lid	Fitting
OC0055-23	55 gallon - 15 deg	w/ bolt-on top	26	23 x 37	8"	1-1/2"
OC0100-23	100 gallon - 15 deg	w/ bolt-on top	36	23 x 63	8"	1-1/2"
OC0145-36	145 gallon - 15 deg	w/ bolt-on top	52	36 x 41	8"	2"
OC0200-36	200 gallon - 15 deg	w/ bolt-on top	78	36 x 53	8"	2"
OC0250-36	250 gallon - 15 deg	w/ bolt-on top	76	36 x 65	8"	2"
OC0325-36	325 gallon - 15 deg	w/ bolt-on top	92	36 x 82	8"	2"

Batch Tank Lids & Stands

Part No.	Capacity	Weight
19502	23" hinged lid	8
19505	36" hinged lid	14
OC023-STP	23" poly cone bottom stand	45
19506	23" poly vertical stand adaptor	7
OC036-STP	36" poly cone bottom stand	92
19507	36" poly vertical stand adaptor	15
CB023-15ST	23" metal stand	37
CB036-15ST	36" metal stand	84

Vertical

Part No.	Capacity	Weight	Dimensions	Lid	Fitting
VT0055-23	55 gallon	26	23 x 38	8"	1"
VT0100-23	100 gallon	36	23 x 64	8"	1"
VT0145-36	145 gallon	52	36 x 40	8"	1"
VT0200-36	200 gallon	58	36 x 53	8"	1-1/2"
VT0250-36	250 gallon	76	36 x 62	8"	1-1/2"
VT0325-36	325 gallon	92	36 x 81	8"	2"

Cone Bottom

Part No.	Capacity	Weight	Dimensions	Lid	Fitting
CB0055-23	55 gallon	26	23 x 36	8"	1-1/2"
CB0100-23	100 gallon	36	23 x 62	8"	1-1/2"
CB0145-36	145 gallon	52	36 x 43	8"	2"
CB0200-36	200 gallon	58	36 x 55	8"	2"
CB0250-36	250 gallon	76	36 x 69	8"	2"
CB0325-36	325 gallon	92	36 x 84	8"	2"

Cone Bottom - Open Top

Part No	Capacity		Weight	Dimensions	Lid	Fitting
OC0055-23	55 gallon - 15 deg	with bolt-on top	26	23 x 37	8"	1-1/2"
OC0100-23	100 gallon - 15 deg	with bolt-on top	36	23 x 63	8"	1-1/2"
OC0145-36	145 gallon - 15 deg	with bolt-on top	52	36 x 41	8"	2"
OC0200-36	200 gallon - 15 deg	with bolt-on top	78	36 x 53	8"	2"
OC0250-36	250 gallon - 15 deg	with bolt-on top	76	36 x 65	8"	2"
OC0325-36	325 gallon - 15 deg	with bolt-on top	92	36 x 82	8"	2"

Commercial Grade Plastic Tanks

Open Top Containment Tanks

Open top tanks are selected for collection systems, temporary liquid storage or as secondary containment for tanks in indoor or outdoor stationary installation. Tanks are manufactured from medium- or high-density polyethylene with U.V. inhibitors. Tank walls are translucent for level viewing and equipped with gallon indicators. Fittings are not furnished unless indicated. Specific gravity is listed below.

Part No.	Capacity		Specific Gravity	Weight	Dimensions (diameter x height)
OP0055-2DC	55 gallon	(2) drums	1.7	70	34 x 62 x 26
OP0055-23	55 gallon	vertical w/bolt on top	2.0	26	23 x 36
OP0100-223	100 gallon	vertical w/bolt on top	2.0	36	23 x 62
OP0145-36	145 gallon	vertical w/bolt on top	2.0	52	36 x 39
OP0200-RT	200 gallon	rectangle	1.7	78	66 x 78 x 12
OP0200-36	200 gallon	vertical w/bolt on top	2.0	58	36 x 51
OP0210-40	210 gallon		2.0	52	40 x 42
OP0250-36	250 gallon	vertical w/bolt on top	2.0	76	36 x 63
OP0325-RT	325 gallon	rectangle	1.7	115	60 x 96 x 24
OP0325-36	325 gallon	vertical w/bolt on top	2.0	92	36 x 80
OP0360-48	360 gallon		2.0	115	48 x 48
OP0500-56	500 gallon	vertical w/bolt on top	2.0	150	56 x 65
OP0625-RT	625 gallon	rectangle	1.7	145	72 x 108 x 24
OP0825-RT	825 gallon	rectangle	1.7	276	73 x 73 x 66
OP0900-86	900 gallon		1.7	175	86 x 43
OP1000-74	1000 gallon	vertical w/bolt on top	1.7	277	74 x 64
OP1200-86	1200 gallon		1.7	200	86 x 54
OP1325-RT	1325 gallon	rectangle	1.7	360	84 x 84 x 60
OP1350-86	1350 gallon		1.7	217	86 x 62
OP1500-86	1500 gallon		1.7	240	86 x 68
OP1700-90	1700 gallon		1.7	317	90 x 66
OP2000-RT	2000 gallon	rectangle	1.7	570	96 x 96 x 68
OP2200-90	2200 gallon		1.7	365	90 x 85
OP2700-90	2700 gallon		1.7	480	90 x 103
OP3300-102	3300 gallon		1.7	550	102 x 105
OP3700-96	3700 gallon	optional bolt on top	1.7	625	96 x 128
OP6800-120	6800 gallon	optional bolt on top	1.7	1525	120 x 146

Commercial Grade Plastic Tanks

Pickup Tanks

Pickup tanks are selected as applicator tanks or when transportable (non DOT regulated) containment is required. Tanks are designed to fit most pickup trucks. Tanks are manufactured from medium-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid	Fitting
PU0200-52	200 gallon	54	52 x 30	8″	2″
PU0205-52	205 gallon	87	52 x 52 x 26	7″	2″
PU0305-60	305 gallon	107	60 x 58 x 30	7″	2″
PU0350-62	350 gallon	92	62 x 34	8″	2″
PU450-62	450 gallon	102	62 x 41	8″	2″





Stock Tanks

Stock tanks are designed for portable livestock watering. Tank tops, side and bottom are ribbed for strength. Drain plug is provided on all tanks except the 124 model. Tank models are nestable for shipping and storage. Tanks are manufactured from USDA compliant low-density polyethylene with U.V. inhibitors and designed for containment of liquids of up to 1.0 specific gravity.

Part No.	Model No.	Capacity	Drain Plug	Weight	Dimensions (diameter x length x height)
ARM-10115	RE214	50 gallon oval	no outlet	15	50 x 31 x 12
ARM-10116	RE224	100 gallon oval	1″	25	55 x 31 x 25
ARM-19455	R42	120 gallon round	1-1/2″	32	48 x 24
ARM-10117	RE226	150 gallon oval	1″	46	75 x 31 x 25
ARM-10138	R62	320 gallon round	1-1/2″	62	72 x 24
ARM-10139	R82	610 gallon round	1-1/2″	92	96 x 24
ARM-10135	R92	920 gallon round	1-1/2″	137	106 x 29

Commercial Grade Plastic Tanks

Spot Sprayer Tanks

Spot sprayer tanks are designed as portable applicator supply tanks and are equipped with pump and equipment mount inserts. Tanks are equipped with molded in legs to support the tank and band locators for tie down. Tanks mount with bottom inserts. Tanks are manufactured from linear low-density polyethylene with U.V. inhibitors and designed for the containement of liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity		Weight	Dimensions (width x length x height)	Lid
SM0014-14S	14 gallon	with sump	8	14 x 30 x 14	5"
SS0014-14	14 gallon	without sump	8	14 x 30 x 14	5"
SM0025-18S	25 gallon	with sump	14	18 x 34 x 18	5"
SS0025-18	25 gallon	without sump	14	18 x 34 x 18	5"





Blow Molded Applicator Tanks

Blow molded applicator tanks are designed with injection-molded leg inserts that allow the tanks to be anchored for transportable applications. They are furnished with brass inserts for pump and wand clip mounting. Tanks are manufactured from high-density polyethylene with U.V. stabilizers and designed for containment of liquids up to 1.7 specific gravity. Tanks are equipped with US gallon and metric indicators for liquid level viewing. These tanks are available in white or yellow.

Part No.	Capacity	Weight	Dimension (width x length x height)	Lid
SB00040	40 gallon	18	24 x 36 x 19	5"
SB00060	60 gallon	21	24 x 36 x 26	5"

Commercial Grade Plastic Tanks

Stackable Totes

Stackable totes can be used for indoor or outdoor, stationary or portable applications (non DOT regulated). Four lift lugs are provided for lifting each tote and a 4-way forklift accessible skid is available for easy handling. Each tote features three 2" threaded ports for dispensing the totes contents. Tanks are manufactured from medium-density polyethylene with UV stabilizers. Specific gravity is listed below.

Part No.	Capacity	Specific Gravity	Weight	Dimensions (width x length x height)	Lid
ST0035-32	35 gallon	1.5	30	32 x 32 x 15	7"
ST0070-32	70 gallon	1.5	42	32 x 32 x 25	7"
ST0120-32	120 gallon	1.5	77	32 x 32 x 38	7"





Stackable Tote Accessories

Part No.	Description	Capacity	Weight	Dimensions (width x length x height)
ST70-120-SK	skid	35, 70, or 120 gallons	50	30 x 30 x 8
ST024-LG	24" leg kit	35, 70, or 120 gallons	24	5 x 5 x 26
ST036-LG	36" leg kit	35, 70, or 120 gallons	70	8 x 8 x 41
ST70-120-DT	drip tray	35, 70, or 120 gallons	15	5 x 20 x 35
ST70-120-PL	plumbing kit	35, 70, or 120 gallons		

Commercial Grade Plastic Tanks

Pallet Paks

Pallet pak units are designed for light-duty transport (non DOT regulated) for indoor or outdoor applications. The base of the pallet frame is designed for forklift transportability. The rectangular pallet paks have a metal frame and plastic base. The vertical paks have poly bases. The tanks are manufactured from medium-density poylethylene with UV inhibitors and are designed for containment of liquids up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions	Lid	Fitting
SP0150-PP	150 gal pallet pak (1) 150 gal tank, pallet & frame	201	26 x 43 x 47	32 x 32 x 15	2″
SP0150-2TPP	150 gal pallet pak (2) 150 gal tank, pallet & frame	356	50 x 43 x 47	32 x 32 x 25	2″
SP0300-PP	300 gal pallet pak (1) 300 gal tank, pallet & frame	316	50 x 43 x 47	32 x 32 x 38	2″
VT0110-PP	110 gal pallet & tank	68	33 x 40 x 44	18 x 34 x 18	2″ top (molded in)
VT0210-PP	210 gal pallet & tank	84	41 x 52	8″	2″ top (molded in)

Pallet Tanks Only

Part No.	Capacity	Weight	Dimensions	Lid	Fitting
SP0150-PPTK	150 gal rectangle	80	24 x 40 x 42	7″	2″
SP0300-PPTK	300 gal rectangle	120	48 x 40 x 42	7″	2″
VT0110-32	110 gal tank only	40	32 x 41	5″	2″ top (molded in)
VT0210-40	210 gal tank only	56	40 x 49	5″	2″ top (molded in)

Fuel Tanks

Typically used as a fuel tank on power equipment, these specialty tanks are manufactured from high-density cross-linked polyethylene with UV stabilizers and are available in natural and black colours. Tanks are designed for the containment of all chemicals (including gasoline and diesel fuels) rated for contact with cross-linked polyethylene. The standard weight tank is designed for chemicals with a secific gravity of 1.75. Tanks are provided with a collection cump on the bottom for fitting installation, but because of the variety of applications, no fittings are furnished. Please consult factory regarding available fittings.

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid
SP0006-FU	6 gal fuel XLPE	5	10 x 15 x 10	2″
SP0006-FUWB	6 gal fuel XLPE w/ 1/4″ brass bulkhead	5	10 x 15 x 10	2″
SP0012-FU	12 gal fuel XLPE	9	14 x 18 x 12	2″
SP0012-FUWB	12 gal fuel XLPE w/ 1/4″ brass bulkhead	9	14 x 18 x 12	2″

Commercial Grade Plastic Tanks

Specialty Bulk Storage and Applicator Tanks

Specialty tanks are available for a variety of custom applications in both stationary and portable configurations. Tanks are manufactured from medium-density polyethylene with UV inhibitors and designed for containment opf liquids of up to 1.7 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Rinse Tanks

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Spinweld
SP002.5-RT	2.5 gal rectangle	3	7 x 15 x 14	5"	3/4"
SP0003-RT	3 gal rectangle	3	7 x 12 x 14	5"	3/4"
SP003.5-CL	3.5 gal cylinder	4	11 x 15	5"	3/4"
SP0004-SQ5	4 gal square	4	11 x 11 x 15	5"	1-1/4"
SP0004-SQ8	4 gal square	4	11 x 11 x 14	8"	1-1/4"
SP0005-SQ5	5 gal square	6	11 x 11 x 20	5"	1-1/4"
SP0005-SQ8	5 gal square	6	11 x 11 x 18	8"	1-1/4"
SP0010-SQ8	10 gal square	10	13 x 13 x 21	8"	1-1/4"



Rectangle Tanks - Flat Bottom

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
SP0005-RT	5 gal	5	10 x 22 x 8	5"	
SP0006-2P	6 gal w/ pump mount & 2" lid	5	12 x 15 x 8	2"	
SP0006-5N	6 gal w/ 5" lid	5	12 x 15 x 8	5"	
SP0007-RT	7 gal	7	9 x 14 x 15	5"	
SP0016-MM	16 gal	9	14 x 21 x 14	8"	
SP0020-OM	20 gal upright	16	11 x 15 x 31	5"	1/2" outlet



Applicator Tanks - Sump On Bottom

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
SP0008-VM	8 gal loaf	6	12 x 16 x 17	5"	1/2" FPT BOSS
SP0012-RT	12 gal rectangle	9	14 x 18 x 12	5"	3/4"
SP0012-VM	12 gal loaf	9	12 x 16 x 22	5"	1/2" FPT BOSS
SP0019-VM	19 gal loaf	15	12 x 16 x 28	5"	1/2" FPT BOSS
SP0020-LC	20 gal rectangle	11	14 x 28 x 12	5"	3/4"



Commercial Grade Plastic Tanks

Utility Tanks - Flat Bottom

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
SP0026-RT	26 gal rectangle	14	18 x 25 x 19	8"	3/4" outlet
SP0045-AS	45 gal rectangle	22	18 x 37 x 19	5"	
SP0050-RT	50 gal rectangle	25	19 x 38 x 23	8"	1"
SP0055-MM	55 gal rectangle	30	18 x 18 x 44	5"	1"
SP0080-RT	80 gal rectangle (support req.)	42	18 x 27 x 44	5"	1"
SP0100-RT	100 gal rectangle	48	27 x 43 x 29	8"	1"
SP0150-RT	150 gal rectangle	60	36 x 48 x 29	8"	1"
SP0200-RT	200 gal rectangle	80	36 x 48 x 38	8'	1"
SP0250-UT	250 gal rectangle	113	29 x 62 x 42	16"	1-1/2"
SP0300-UT	300 gal rectangle	159	29 x 62 x 53	16"	1-1/2"
SP0400-UT	400 gal rectangle	207	29 x 62 x 66	16"	2"





Low Profile Rectangle Tanks

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
LP0050-RT	50 gal low profile rectangle	35	24 x 43 x 15	5"	1"
LP0068-RT	68 gal low profile rectangle	40	26 x 42 x 17	6"	1"
LP0110-RT	110 gal low profile rectangle	59	35 x 48 x 19	5"	1"
LP0200-RT	200 gal low profile rectangle	84	48 x 60 x 19	8"	1"
LP0300-RT	300 gal low profile rectangle	135	48 x 80 x 21	8"	2"

Rectangle Tanks - Total Drain

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
SP0035-RT	35 gal rectangle	17	19 x 28 x 20	5"	1"
SP0056-RT	56 gal rectangle	30	20 x 38 x 26	5"	3/4"

Commercial Grade Plastic Tanks

PCO (Pest Control Operator) Tanks

PCO tanks can be selected for stationary or transportable (non DOT) regulated applications both indoors and outdoors. The 50-300 gallon tanks have a rounded bottom for best fluid drainage. A 2" deep sump option is also available on these sizes. PCO tanks must be securely anchored for use in transportable applications and powder coated steel bands are available for this purpose. The tanks are manufactured from medium-density polyethylene with UV stabilizers and designed for containment of liquids of up to 1.7 specific gravity.

Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
PCO035-16W	35 gallon	25	16 x 35 x 21	5"	1"
PCO050-19S	50 gallon w/ sump	25	19 x 38 x 23	8"	1"
PCO050-19W	50 gallon	25	19 x 38 x 23	8"	1"
PCO0100-30S	100 gallon w/ sump	50	30 x 38 x 29	8"	1"
PCO0100-30W	100 gallon	50	30 x 38 x 29	8"	1"
PCO0150-37S	150 gallon w/ sump	61	37 x 48 x 29	12"	1-1/4"
PCO0150-37W	150 gallon	61	37 x 48 x 29	12"	1-1/4"
PCO0200-37S	200 gallon w/ sump	82	37 x 48 x 38	12"	1-1/4"
PCO0200-37W	200 gallon w/ sump	82	37 x 48 x 38	12"	1-1/4"
PCO0300-37S	300 gallon w/ sump	160	37 x 69 x 40	16"	2"
PCO0300-37W	300 gallon w/ sump	160	37 x 69 x 40	16"	2"





Powder Coated Steel Bands

Part No.	Capacity	Weight	Dimensions (width x length)
PC0035-SB	35 gallon set	3	2 x 50.5
PC0050-SBP	50 gallon set	6	2.5 x 57.5
PC0100-SBP	100 gallon set	20	2.5 x 76
PC0150-SBP	150 gallon set	30	3.5 x 82
PC0200-SBP	200 gallon set	36	3.5 x 98
PC0300-SBP	300 gallon set	40	4 x 100

Commercial Grade Plastic Tanks

Water Only Vertical Tanks

Water only vertical tanks are free standing for indoor or outdoors stationary applications. Tanks are manufactured from FDA compliant high-density polyethylene with UV inhibitors. They are designed for the storage of chemicals with a specific gravity of 1.0 or less and available in dark green.

Part No.	Capacity	Specific Gravity	Weight	Dimensions (diameter x height)	Lid	Fitting
WO2500-VT	2500 gallon	1.0	392	96 x 92	16"	2"
WO03000-VT	3000 gallon	1.0	487	96 x 109	16"	2"

Tank Stands

Part No.	Capacity	Weight	Dimensions (diameter x height)
OC023-STP	23" poly (adapter req)	45	30 x 28
19506	23" vertical stand adaptor	7	23 x 5
OC036-STP	36" poly (adaptor req)	92	44 x 30
19507	36" vertical stand adaptor	15	36 x 6
VT38/31-STP	31-1/2" poly	35	39 x 24
VT-ST052	52' poly	165	52 x 36
VT-ST052FF	52" foam filled poly	201	52 x 36
VT160-28ST	160 gallon metal stand	83	30 x 26
VT265-31ST	265 gallon metal stand	89	33 x 26
VT300-35ST	300 gallon metal stand	114	37 x 38

Gusseted Top Vertical Tanks

Gusseted top vertical tanks are free standing with a flat bottom for indoor or outdoor installations. Tanks are manufactured from medium-density polyethylene with UV inhibitors and designed for containment of liquids of up to 1.5 specific gravity. Tank walls are translucent for level viewing and equipped with gallon indicators.

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid	Fitting
GV1050-86	1050 gallon	175	86 x 50	16"	2"
GV1350-86	1350 gallon	207	86 x 62	16"	2"
GV1500-86	1500 gallon	228	86 x 69	16"	2"
GV1650-86	1650 gallon	255	86 x 74	16"	2"

Commercial Grade Plastic Tanks

Septic / Cistern Tanks

Septic tanks are designed and manufactured to meet wastewater treatment system standards. Cistern water tanks are designed for bulk storage or collection of potable water. Manufactured from high-density polyethylene with UV inhibitors, tanks are designed for containment of liquids up to 1.7 specific gravity. Tanks feature deep ribbing for strength to permit below-ground installations of up to 36" depths. The 1000, 1250, and 1500 gallon double-compartment septic tanks have been tested by NSF to meet the IAPMO Z1000 and CAN/CSA-B-66 standarsd. Consult with the applicable state, province, or local codes for polyethylene septic tank compliance and installation requirements.



Septic Tanks

Part No.	Capacity	Description	Weight	Dimensions (width x length x height)
AST-0300-1	300 gallon	pump tank w/one access cover	134	54 x 56
AST-0500-1	500 gallon	pump tank w/one access cover	197	63 x 74
AST-0750-1	750 gallon	single compartment w/one access cover	259	60 x 70 x 60
AST-1000-1	1000 gallon	single compartment w/two access cover	390	60 x 101 x 60
AST-1000-2	1000 gallon	double comparment w/two access cover	436	60 x 101 x 60
AST-1250-1	1250 gallon	single compartment w/two access covers	443	58 x 118 x 72
AST-1250-2	1250 gallon	double compartment w/two access covers	489	58 x 118 x 72
AST-1500-1	1500 gallon	single compartment w/two access covers	528	58 x 137 x 72
AST-1500-2	1500 gallon	double compartment w/two access covers	574	58 x 137 x 72

Cistern Tanks

Part No.	Capacity	Description	Weight	Dimensions (width x length x height)
AST-0325-1W	325 gallon	cistern tank	134	54 x 56
AST-0525-1W	525 gallon	cistern tank	194	63 x 74
AST-0850-1W	850 gallon	cistern single compartment	259	60 x 70 x 60
AST-1150-1W	1150 gallon	cistern single compartment	414	60 x 101 x 60
AST-1450-1W	1450 gallon	cistern single compartment	473	58 x 118 x 72
AST-1700-1W	1700 gallon	cistern single compartment	567	58 x 137 x 72

Commercial Grade Plastic Tanks

Septic / Cistern Tank Accessories

Only Ace tanks have double-walled access covers that lock securely to the tank body and can be secured using nylong ties, eliminating the need for metal fasteners that can corrode and fail. They feature a custom-molded gasket in the lid. Manufactured from extruded nitrile rubber, the gasket snaps into the lid to make a watertight seal.

Aquifer Low Profile Cistern Tanks

Aquifer low profile cistern tanks are designed to provide a safe and durable means for the storage of potable or non-potable water. Their sectional ribbing design will sustain vertical soil pressures of up to 400 PSF. Tanks can be buried up to 28" deep and can be backfilled empty. Multiple fitting locations are provided to accommodate a variety of plumbing configurations. Manufactured from high density poylethylene with UV inhibitors. Aquifers are made from FDA compliant resins and conform to the requirements of NSF/ANSI Standard 61. Designed for the containment of liquids of up to 1.7 specific gravity. Tanks are available with burial lid or ground access assembly options.



Part No.	Capacity	Weight	Dimensions (width x length x height)
ACT1000-LPB	1000 gall on w/ burial lid	559	98 x 111 x 36
ACT1000-LPG	1000 gallon w/ ground access assembly	595	98 x 111 x 36
ACT1500-LPB	1500 gallon w/ burial lid	702	98 x 111 x 48
ACT1500-LPG	1500 gallon w/ ground access assembly	738	98 x 111 x 48
ACT2000-LPB	2000 gallon w/ burial lid	917	98 x 158 x 45
ACT2000-LPG	2000 gallon w/ ground access assembly	953	98 x 158 x 45
ACT2500-LPB	2500 gallon w/ burial lid	1031	98 x 158 x 54
ACT2500-LPG	2500 gallon w/ ground access assembly	1067	98 x 158 x 54

Commercial Grade Plastic Tanks

Tractor Mounted Tanks



Tractor mounted tanks are designed as portable (non DOT regulated) applicator tanks. Tanks require the bottom to be fully supported with a cradle for use. Gallon indicators are included and the tank walls are translucent for level viewing. Ends of tanks feature fitting flats to facilitate a variety of installation options. Bottoms of tanks feature a collection sump for full drain out. Tanks are manufactured from medium density polyethylene with UV inhibitors and designed for containment of liquids of up to 1.7 specific gravity.

Oval Tanks

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid	Fitting
OT0300-31	300 gallon oval	100	31 x 49 x 56	16"	3/4" & 1-1/4"

Tear Drop Tanks

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid	Fitting
TD0250-36	250 gallon	97	36 x 52 x 45	12"	3/4" & 1-1/4"
TD0300-36	300 gallon	109	36 x 62 x 45	12"	3/4" & 1-1/4"

Cradles

Part No.	Capacity	Weight	Bands
TD0250-C	250 gallon	96	2.5" X 74.5"
TD0300-C	300 gallon	108	2.5" x 74.5"



Cut-away Applicator Tanks

Part No.	Capacity	Weight	Dimensions (diameter x height)	Lid	Fitting
CAW0200-24	200 gallon	80	24 X 55 X 46	8"	3/4" & 1-1/4"
CAW0250-24	250 gallon	95	24 X 61 X 51	8"	3/4" & 1-1/4"

Cut-away Cradles

Part No.	Capacity	Weight	Bands
CAW0200-C	200 gallon	135	3" X 60"; 3" X 40"
CAW0250-C	250 gallon	143	3" X 72"; 3" X 51"



Commercial Grade Plastic Tanks

Crop Care Tanks

Crop care tanks are designed for OEM sprayer applications that contain chemicals rated for contact with poylethylene. Hoop recesses are provided around the tank to facilitate installation and anchoring. Wide bottom tanks are cutout on each side to facilitate narrow track widths and are only available with a cloped-style sump. Larger tanks are furnished with polyethylene baffles for fluid control and a five-gallon rinse tank. The tanks are manufactured from high-density polyethylene with UV stabilizers and are designed for liquids of up to 1.9 specific gravity.



Part No.	Capacity	Weight	Dimensions (width x length x height)	Lid	Fitting
CM0500-48	500 gallon w/sump	202	48 x 90 x 38	16″	2″
CM0750-48	750 gallon w/sump	262	48 x 90 x 50	16″	2″
CC1000-58S	1000 gallon w/ sloped sump	345	58 x 115 x 47	16″	2″
CC1000-58N	1000 gallon narrow bottom w/ sloped sump	345	58 x 115 x 51	16″	2″
CC1000-58B	1000 gallon w/ box sump	350	58 x 115 x 47	16″	2″
CC1250-58S	1250 gallon w/ sloped sump	480	58 x 115 x 57	16″	2″
CC1250-58N	1250 gallon narrow bottom w/ sloped sump	480	58 x 115 x 61	16″	2″
CC1250-58B	1250 gallon w/ box sump	485	58 x 115 x 57	16″	2″
CC1500-58S	1500 gallon w/ sloped sump	550	58 x 115 x 66	16″	2″
CC1500-58N	1500 gallon narrow bottom w/ sloped sump	550	58 x 115 x 70	16″	2″
CC1500-58B	1500 gallon w/ box sump	550	58 x 115 x 66	16″	2″

Hoops

Part No.	Capacity	Kit
CC0500-HP	500 gallon hoop	1 hoop 1 2/3″ pipe
CC0750-HPS	750 gallon hoop	1 hoop 1 2/3″ pipe
CC1000-HP	1000 gallon hoops	1 set 3 - 2 3/8″ pipes
CC1250-HP	1250 gallon hoops	1 set 3 - 2 3/8″ pipes
CC1500-HP	1500 gallon hoops	1 set 5 - 2 3/8″ pipes



Accessory Parts

Fittings

Browse a wide variety of accessories, lids & fittings to meet the needs of our customers. Our polypropylene bulkhead fittings incorporate an innovative design that is proven to last.

Features:

- Retainer ring molded into each fitting prevents the sealing gasket from expanding or sliding out of position under compression.
- Bearing washer insures even compression on the gasket and promotes sealing.
- Each fitting features left hand compression threads to prevent loosening while installing mating fittings.
- Internal threads feature female pipe threads and are provided on both sides of the fitting - mating fittings can be installed on both sides of the installed fittings.
- Sealing gaskets are produced from durable Santoprene thermoplastic rubber (TPR)
- Fitting compression nuts feature a specially designed cross-section to prevent distortion under load.

Bulkhead Fittings & Syphon Tubes

Part No.	Description	Hole requirement
10897	1/4" brass bulkhead	25/32"
10058	1/2" ace bulkhead	1-1/4"
10025	1/2" polypropylene bulkhead	1-3/8"
13208	3/4" ace bulkhead	1-7/16"
10484	3/4" ace heavy duty bulkhead	1-3/4"
10501	3/4" polypropylene bulkhead	1-3/8"
10485	1" ace bulkhead	1-3/4"
10503	1" polypropylene bulkhead	2-1/4"
10918	1-1/4" ace bulkhead	2-1/4"
10507	1-1/2" ace bulkhead	3"
10508	2" ace bulkhead	3"
10486	2" stainless steel bulkhead double threaded	3"
10912	2" ace heavy duty bulkhead for tanks over 3000 gal	3-1/4"
10490	2" stainless steel bulkhead heavy for tanks over 3000 gal	3-1/4"
12528	3" ace bulkhead	4-1/2"
10487	3" stainless steel bulkhead double threaded	4-1/2"
10511	2" syphon tube	

Accessory Clips

Part No.	Description
19444	5/16" accessory clip
12100	5/16" accessory clip kit
12732	1/2" accessory clip
12200	1/2" accessory clip kit



Accessory Parts

Lids

These durable lids are available in a wide range of sizes from 2" to 22". Most are available with or without venting to suit your applications. Injection molded from polypropylene with UV inhibitors ensures long life.

Part No.	Description
10631	2" spin-on kelch cap
13108	3-1/2" lid and lanyard assembly
10523	5" spin-on non-vented lid
10522	5" spin-on spring-vented lid
12110	5" spin-on lid w/ step vent
19406	5" hinged low-profile lid
12415	7" spin-on non-vented lid
12414	7" spin-on spring-vented lid
12427	7" spin-on lid w/ step vent
10525	8" threaded vented lid & ring
10526	12" threaded vented lid & ring
10527	12" threaded vented lid & ring
10528	16" threaded vented lid & ring
10530	22" threaded vented lid & ring
10520	breather only (for 8" & 12" lids)
10529	breather , 4" center (for 16" lid)
12460	self-anchoring lanyard - 12"
10873	short lanyard - 12"
10534	long lanyard - 16"
19024	outlet cap, 3/4"
19025	tether for outlet cap
10960	gasket for outlet cap



Spinwelds

DHI spinwelds feature a hex driving recess to ease installation. This driving recess makes the installation tools universal and easy to construct. These spinwelds also feature a specially designed conical welding surface that helps to center the spinweld and increases the surface welding area.

Part No.	Description
10237	3/8" threaded plug
10041	3/8" threaded spinweld
12104	3/4" patch (9/16" hex drive)
10008	1" patch (3/4" hex drive)
12429	1-1/2" patch (3/4" hex drive)
10441	2" patch (3/4" hex drive)

Utility Tanks

T-Tanks / Box-Shaped Tanks

Available in three types: (1) regular, (2) extra heavy, and (3) marine.

Product	Capacity			Outside Dimensions		
	Imp Gal	Ltr	USG	Length	Width	Height
T-5	5	23	6	15 3/4″	11 3/4″	7 3/4″
T-6	6	27	7	19 3/4″	12″	7″
T-7	7	32	8	23 3/4″	10″	8″
T-8	8	36	10	18″	16″	8″
T-10	10	46	12	24″	16″	8″
T-13	13	59	16	30″	16 1/2″	8″
T-14	14	64	17	18″	18″	12″
T-15	15	68	18	30″	12″	12″
T-16	16	73	19	42″	12″	9″
T-18.5	18.5	84	22	33″	17″	9″
T-21	21	96	25	35″	14″	12″
T-23	21	105	28	31″	21″	10″
T-25	25	114	30	21 3/4″	19 1/2″	16″
T-26	26	118	31	48″	17″	9″
T-30*	30	136	36	53″	16″	10″
T-32*	32	146	39	36″	18″	14″
T-33	33	150	40	49″	16″	11 1/2″
T-55*	55	250	66	38″	25 1/2″	15″
T-85*	85	387	102	41″	28″	21″
T-115*	115	523	138	48″	30″	24″
BT 20 (bow tank)	20	90	24	diagram available from Century Plastics Ltd		





Utility Tanks

Open Top Liquid Storage Tanks

Canadian Product #	American product #	Imp Gal	Ltr	USG	Diameter - outside lip	Height
OT-45	OT-55	45	204	55	27″	30″
OT-45-L	OT-55-L	45	204	55	27″	30″
OT-85-L	OT-102-L	85	386	102	29″	49″
OT-100-L	OT-120-L	100	454	120	32.5″	44″
OT-200	OT-240	200	908	240	44″	45.5″
OT-400	OT-480	400	1816	480	57″	50″

*CSA certified NSF/ANSI 61



Bushel Bins

Product	Imp Gal	Ltr	USG	Length	Width	Height
BB-8	66	300	79	39″	27.25″	23″
BB-14	108	490	130	46″	34″	27″
BB-18	140	635	168	56″	34″	28″
Super shipper*	28	125	33	45″	23″	15″

*Available with or without lids

Valves & Couplers

Ball Valves

Bolted Ball Valves

- Manufactured from glass re-inforced polypropylene for strength and durability - will never rust or corrode.
- Self-aligning ball rotates freely against Teflon seats.
- Unique body-to-flange design allows for low torque on/off operation.
- Viton O-ring stem seal and EPDM O-ring body seal.
- Available with blue Norwesco handle or blank yellow handle.
- Pressure rates at 125 PSI @ 70°F.
- All valves tested by air pressure under water.

Recommended operating pressure

1/2" thru 3": 100 PSI @0°F / 125 PSI @ 70°F / 70 PSI @ 150°F
4": 70 PSI @ 0°F / 90 PSI @ 70°F / 50 PSI @ 150°F

Item Code	Description	Blue Handle Part No	Yellow Handle Part No	Standard Packaging
A	1/2" full port	60540	61115	24
A	3/4" full port	60541	61116	24
A	1" standard port	60542	61117	24
A	1" full port	60543	61118	24
A	1 1/4" standard port	61734	61119	24
A	1 1/4" full port	60527	61120	24
A	1 1/2" full port	60526	61121	24
D	1 1/2" full port nozzle	60544	61125	12
A	2" standard port	60529	61122	24
C	2" standard port M x F	62046	-	24
D	2" standard port nozzle	60545	61126	12
B	2" full port	60528	61123	12
C	2" full port M x F	61876	-	12
D	2" full port nozzle	60546	61127	9
B	3" full port	61720	61124	8
C	3" full port M x F	62047	-	8
E	4" full port	62787	62788	4





Valves & Couplers

Ball Valves

Compacted Bolted Ball Valves

- Male pipe thread end flange and cam action coupler end flange eliminate the need for additional fittings.
- Manufactured from glass re-inforced polypropylene for strength and durability - will never rust or corrode.
- Self-aligning ball rotates freely against Teflon seats.
- Unique body-to-flange design allows for low torque on/off operation.
- Viton O-ring stem seal and EPDM O-ring body seal.
- Available with blue Norwesco handle or blank yellow handle.
- Pressure rates at 125 PSI @ 70°F.
- All valves tested by air pressure under water.



Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Blue Handle Part No	Yellow Handle Part No	Standard Packaging
F	2" full port M x F	62286	62308	12
G	2" full port F x F	62287	62309	12
H	2" full port M x M coupler	62288	62310	12
I	2" full port F x M coupler	62314	62313	12

Single Union Ball Valve

- Manufactured from polypropylene.
- Teflon seats.
- EPDM O-rings (viton kits available).
- Pressure rated at 125 PSI @ 70°F.
- All valves tested by air pressure under water.

Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
A	1/2" single union	60409	24
A	3/4" single union	60410	24
A	1" single union	60411	24
A	1 1/4" single union	60412	12
A	1 1/2" single union	60413	12
A	2" single union	60414	12
A	3" single union	60415	4
B	1" 45 nozzle valve	60479	24

Valves & Couplers

Ball Valves

Multi-Port Ball Valves

- Manufactured from polypropylene.
- Teflon seats.
- EPDM O-rings (viton kits available).
- Pressure rated at 125 PSI @ 70°F.
- All valves tested by air pressure under water.
- Three position settings: bottom-to-right, bottom-to-left or off.



Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
C	3/4" true union (full port)	60417	24
D	2" multi-port (standard port)	60418	12

Stainless Steel Ball Valves

- Manufactured from 316 stainless steel.
- Full port construction.
- Water, oil and gas rated to 1000 PSI.
- Locking handle.
- Teflon seats and seals.
- Polished stainless steel ball for precise operation.
- Tested by air pressure under water.



Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item code	Description	Part No.
E	3/8" full port	60480
E	1/2" full port	60481
E	3/4" full port	60482
E	1" full port	60483
E	1 1/4" full port	60484
E	1 1/2" full port	60485
E	2" full port	60487
E	3" full port	60488

Valves & Couplers

Couplers, Adapters, Switch Adapters, King Nipples, & Hose Barbs

Cam Action Coupler and Adapters

- Manufactured from glass reinforced polypropylene.
- Smooth operating stainless steel cam arms and pins.
- Standard with EPDM gaskets.
- Interchageable with other couplers and adapters.

Recommended operating pressure

1/2" thru 3": 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F
3" and 4": 70 PSI @ 0°F / 90 PSI @ 70°F / 50 PSI @ 150°F

Item Code	Description	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	4"
A	male adapter - female thread	61199	61207	61215	61223	61231	61239	61247	62789
B	female coupler - amle thread	61255	61259	61263	61267	61271	61275	61279	62790
C	female coupler - hose shank	61256	61260	61264	61268	61272	61276	61280	62791
D	female coupler - female thread	61257	61261	61265	61269	61273	61277	61281	62792
E	male adapter - hose shank	61203	61211	61219	61227	61235	61243	61251	62793
F	male adapter - male thread	61204	61212	61220	61228	61236	61244	61252	62794
DC	dust cap for male adapter	61258	61258	61266	61274	61274	61278	61282	62795
DP	dust plug for female coupler	61214	61214	61222	61238	61238	61246	61254	62796



Valves & Couplers

Couplers, Adapters, Switch Adapters, King Nipples, & Hose Barbs

90° *Cam Action Couplers and Adapters*

- Manufactured from glass reinforced polypropylene.
- Reduces the number of joints in piping applications.
- Smooth operating stainless steel cam arms and pins.
- Standard with EPDM gaskets.
- Interchangeable with other couplers and adapters.
- Pressure rating 125 PSI @ 70°F



Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item code	Description	Size and part no.	
		1 1/2"	2"
90A	male adapter with female thread	61293	61296
90C	female coupler with hose shank	61299	61301
90D	female coupler with female thread	61300	61302
90F	male adapter with male thread	61289	61291

Switch Adapters

- Manufactured from glass reinforced polypropylene.
- Allows quick changing of spray nozzles
- Self-aligning grooves

Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
E	3/4" x 1/4"	61326	24
E	3/4" x 3/8"	61327	24

Valves & Couplers

Couplers, Adapters, Switch Adapters, King Nipples, & Hose Barbs

King Nipples

- King nipples manufactured from glass reinforced polypropylene.

Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
F	1 1/2"	61319	24
F	2"	61861	24
G	3"	61321	24
G	4"	62468	-



F



G



H

Hose Barbs

- Hose barbs manufactured from polypropylene.

Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
H	1/2"	61303	50
H	3/4"	61304	50
H	1"	61305	25
-	1 1/4" MPT X 1" HB elbow	62469	-

Valves & Couplers

Flange Ball Valves & Fittings

- Quick and easy assembly. No pipe tape or sealant necessary.
- Positive seals.
- Easy on/off hose connections.
- 360 orientation
- Valves and fittings are manufactured from glass reinforced polypropylene for strength and durability - will never rust or corrode.



Valves

- Self aligning ball rotates freely against Teflon seats.
- Unique body-to-flange design allows for low torque on/off operation.
- Viton O-ring stem seal and EPDM O-ring body seal
- Available with blue Norwesco handle or blank yellow handle.
- Pressure rated at 125 PSI @ 70F.
- All valves tested by air pressure under water.

Recommended operating pressure 100 PSI @ 0°F / 125 PSI @ 70°F / 70 PSI @ 150°F

Item Code	Description	Blue Handle Part No	Yellow Handle Part No	Standard Packaging
A	1" full port flange x flange (4 bolt)	63027	63028	24
A	2" full port compact flange x flange (4 bolt)	63122	63123	12
A	3" full port flange x flange (6 bolt)	63124	63125	8

Stainless Steel Worm Screw Hose Clamps for Flange Fittings

Item code	Description	Part No.
B	1"	62932
B	2"	62933
B	3"	62934

EPDM Flange Gasket for Flange Fittings

Item code	Description	Part No.
B	1"	62932
B	2"	62933
B	3"	62934

Valves & Couplers

Flange Ball Valves & Fittings

1″ Fittings

Item code	Description	Part No.
D	1″ flange tee	62912
E	1″ flange elbow	62913
F	1″ flange coupling	62914
G	1″ flange x 3/4″ MPT	63098
G	1″ flange x 1″ MPT	62915
G	1″ flange x 1 1/4″ MPT	63099
H	1″ flange x 1″ FPT	62916
I	1″ flange x 3/4″ HB	62917
I	1″ flange x 1″ HB	62918
I	1″ flange x 1 1/4″ HB	62919
J	1″ flange x 3/4″ HB 90	62920
J	1″ flange x 1″ HB 90′	62921
J	1″ flange x 1 1/4″ HB 90	62922
K	1″ flange cross	62923
L	1″ flange plug	62924
M	1″ flange plug with 1/4″ FPT	62925

2″ Fittings

Item code	Description	Part No.
D	2″ flange tee	63100
E	2″ flange elbow	63101
F	2″ flange coupling	63102
G	2″ flange x 2″ MPT	63103
H	2″ flange x 2″ FPT	63104
I	2″ flange x 1 1/2″ HB	63105
I	2″ flange x 2″ HB	63106
J	2″ flange x 1/2″ HB 90	63107
J	2″ flange x 2″ HB 90	63108
K	2″ flange cross	63109
L	2″ flange plug	63110
N	2″ flange x 1″ flange reducing coupling	62927
O	2″ flange x 2″ male coupler	62926

3″ Fittings

Item code	Description	Part No.
D	3″ flange tee	63111
E	3″ flange elbow	63112
F	3″ flange coupling	63113
G	3″ flange x 3″ MPT	63114
I	3″ flange x 2″ HB	63115
I	3″ flange x 3″ HB	63116
J	3″ flange x 2″ HB 90	63117
J	3″ flange x 3″ HB 90	63118
K	3″ flange cross	63119
L	3″ flange plug	63120
N	3″ flange x 2″ flange reducing coupling	62928
O	3″ flange x male coupler	63121




Valves & Couplers

SCH80 Polypropylene Fittings

Schedule 80 Threaded Polypropylene Fittings

- Manufactured from glass re-inforced polypropylene for strength and durability.
- Schedule 80 design
- Pressure rated to 150 PSI @ 70F



Recommended operating pressure 120 PSI @ 0°F / 150 PSI @ 70°F / 90 PSI @ 150°F

Tees

Item Code	Description	Part No.	Standard Packaging
A	3/8"	62464	10
A	1/2"	62209	10
A	3/4"	62210	10
A	1"	62211	10
A	1 1/4"	62212	10
A	1 1/2"	62213	-
A	2"	62190	-
A	3"	62214	-

90° Street Elbows

Item Code	Description	Part No.	Standard Packaging
D	3/8"	62460	10
D	1/2"	62243	10
D	3/4"	62244	10
D	1"	62245	10
D	1 1/4"	62246	10
D	1 1/2"	62247	10
D	2"	62199	10
D	3"	62248	-

45° Street Elbows

Item Code	Description	Part No.	Standard Packaging
C	3/4"	62907	10
C	1"	62908	10
C	1 1/4"	62909	10
C	1 1/2"	62910	10
C	2"	62911	10

Crosses

Item Code	Description	Part No.	Standard Packaging
E	3/4"	62262	5
E	1"	62263	5
E	1 1/4"	62264	-
E	1 1/2"	62265	-
E	2"	62202	-

90° Pipe Elbows

Item Code	Description	Part No.	Standard Packaging
B	3/8"	62465	10
B	1/2"	62215	10
B	3/4"	62216	10
B	1"	62217	10
B	1 1/4"	62218	10
B	1 1/2"	62219	-
B	2"	62191	-
B	3"	62220	-

Pipe Couplings

Item Code	Description	Part No.	Standard Packaging
F	3/8"	62461	10
F	1/2"	62237	10
F	3/4"	62238	10
F	1"	62239	10
F	1 1/4"	62240	10
F	1 1/2"	62241	10
F	2"	62194	10
F	3"	62242	-

Valves & Couplers

SCH80 Polypropylene Fittings

Pipe Nipples

Item Code	Description	Part No.	Standard Packaging
	3/8" x short	62459	10
	1/2" x short	62221	10
	1/2" x 3"	62222	10
	3/4" x short	60554	10
G	3/4" x 4"	62223	10
H	3/4" x 6"	62224	10
	1" x short	60555	10
H	1" x 4"	62225	10
H	1" x 6"	62226	10
	1 1/4" x short	60556	10
G	1 1/4" x 4"	62227	10
H	1 1/4" x 6"	62228	10
	1 1/2" x short	62547	10
	1 1/2" x 4"	62229	10
H	1 1/2" x 6"	62230	10
	2" x short	60548	10
G	2" x 4"	62192	10
H	2" x 6"	62193	10
	3" x short	61769	-
H	3" x 6"	62232	-
	4" x short	62467	-

Reducer Bushings

Item Code	Description	Part No.	Standard Packaging
J	3/8" x 1/8"	63604	10
J	3/8" x 1/4"	62466	10
J	1/2" x 1/4"	62267	10
J	1/2" x 3/8"	62268	10
J	3/4" x 1/8"	62268	10
J	3/4" x 1/4"	62270	10
J	3/4" x 3/8"	62271	10
J	3/4" x 1/2"	62272	10
J	1" x 1/8"	62273	10
J	1" x 1/4"	62274	10
J	1" x 1/2"	62275	10
J	1" x 3/4"	62276	10
J	1 1/4" x 3/4"	62277	10
J	1 1/4" x 1"	62278	10
J	1 1/2" x 3/4"	62279	10
J	1 1/2" x 1"	62280	10
J	1 1/2" x 1 1/4"	62281	10
J	2" x 3/4"	62195	10
J	2" x 1"	62196	10
J	2" x 1 1/4"	62197	10
J	2" x 1 1/2"	62198	10
J	3" x 1 1/2"	62282	-
J	3" x 2"	60330	-



G



H

O



Valves & Couplers

SCH80 Polypropylene Fittings

Reducer Nipples

Item Code	Description	Part No.	Standard Packaging
I	1/2" x 3/8"	62455	10
I	3/4" x 1/2"	62233	10
I	1" x 1/2"	62456	10
I	1" x 3/4"	62234	10
I	1 1/4" x 3/4"	62223	10
I	1 1/4" x 1"	62457	10
I	1 1/2" x 1"	62235	10
I	1 1/2" x 1 1/4"	62458	10
I	1" x 6"	62236	10
I	2" x 1 1/2"	60549	10
I	3" x 2"	61768	-
I	4" x 3"	62938	-



I

Pipe Caps

Item Code	Description	Part No.	Standard Packaging
K	1/2"	62462	10
K	3/4"	62250	10
K	1"	62251	10
K	1 1/4"	62463	10
K	1 1/2"	62253	10
K	2"	62200	10
K	3"	62254	-



K

Pipe Plugs

Item Code	Description	Part No.	Standard Packaging
L	1/2"	62255	10
L	3/4"	62256	10
L	1"	62257	10
L	1 1/4"	62258	10
L	1 1/2"	62259	10
L	2"	62201	10
L	3"	62260	-




L

Valves & Couplers

Y-Line & T-Line Strainers


Y-Line Strainers

- Manufactured from glass reinforced polypropylene.
- Smooth operating stainless steel cam arms and pins.
- Standard with EPDM gaskets.
- Interchageable with other couplers and adapters.



Recommended operating pressure

1/2" thru 2": 70 PSI @ 0°F / 90 PSI @ 70°F / 50 PSI @ 150°F
3": 55 PSI @ 0°F / 70 PSI @ 70°F / 40 PSI @ 150°F



Item Code	Description	Part No.	Standard Packaging
A	1/2" with 20 mesh screen	61472	12
A	1/2" with 40 mesh screen	61473	12
A	1/2" with 80 mesh screen	61474	12
A	3/4" with 20 mesh screen	61475	12
A	3/4" with 40 mesh screen	61476	12
A	3/4" with 80 mesh screen	61477	12
A	1" with 20 mesh screen	61478	12
A	1" with 40 mesh screen	61479	12
A	1" with 80 mesh screen	61480	12
A	1 1/4" with 20 mesh screen	61738	12
A	1 1/4" with 40 mesh screen	61740	12
A	1 1/4" with 80 mesh screen	61741	12
A	1 1/2" with 20 mesh screen	61488	12
A	1 1/2" with 40-20 mesh screen	61489	12
A	1 1/2" with 80-20 mesh screen	61490	12
A	2" with 20 mesh screen	61493	12
A	2" with 40-20 mesh screen	61494	12
A	2" with 80-20 mesh screen	61495	12
B	3" with 6 mesh screen	62337	-
B	3" with 12 mesh screen	62338	-
B	3" with 20 mesh screen	62339	-
B	3" with 40 mesh screen	62340	-

Valves & Couplers

Y-Line & T-Line Strainers

T-Line Strainers

- Manufactured from polypropylene.
- Sizes in 1/2", 3/4" and 1"
- 20 to 80 mesh 304 stainless steel screens.

Recommended operating pressure 80 PSI @ 0°F / 100 PSI @ 70°F / 56 PSI @ 150°F

Item Code	Description	Part No.	Standard Packaging
C	1/2" with 20 mesh screen	61459	12
C	1/2" with 40 mesh screen	61460	12
C	1/2" with 80 mesh screen	61461	12
C	3/4" with 20 mesh screen	61464	12
C	3/4" with 40 mesh screen	61465	12
C	3/4" with 80 mesh screen	61466	12
C	1" with 20 mesh screen	61469	12
C	1" with 40 mesh screen	61470	12
C	1" with 80 mesh screen	61471	12

C



Mesh Screen for 3" Y-line strainer

High Density Polyethylene Lids

Description	Item Code	Part No.
22" lid and ring with air vent		63679
22" lid, ventless with ring		63863
16' lid and ring with blue snap-in vent	A	63485
16" lid and ring with 3' center thread		63868
16" lid, ventless with ring		60367
16" lid, ventless with ring	B	60365
16" ring only		60012
Ethafoam gasket for 16" non-hinger lid		62941
Blue snap-in vent for 16" lid (63485)		63539
8" lid with blue snap-in vent	C	63480
Blue snap-in vent for 8" lid (63480)		63482
8" lid, ring and air vent (for 22 vertical and loaf tanks)		60032
5" lid with ball check air vent	D	63484
5" lid with 2" FPT (does not include vent cap)		63264
5" lid, hinger (for 52 and 68 gallon flat bottom and 110 low profile tanks)		63673
EPDM gasket for 5" lid (63264 or 63484)		60366

A



B



C



D



Valves & Couplers

Lids, Lid Accessories, & Repair Kits

Hinged Lid

This lid is manufactured from a co-polymer material for strength, durability, and excellent chemical resistance. Our unique locking tab allows you to easily slip a padlock through it and secure your lid from theft or spills. The lid is interchangeable with a standard 16'" lid and ring assembly if you choose to replace your existing lid.

- Easy open/close - opens a full 180 degrees.
- Comes complete with a baffle vent assembly, allowing for adequate venting when bottom filling your tank.

Description	Item Code	Part No.
22" complete lid assembly	E	63874
16" complete lid assembly	E	62532

High Density Polyethylene Lids

Description	Part No.
16" hinged lid with vent assembly, without ring	62826
16" hinged ventless lid, with ring	63390
Vent assembly	62827
Ring assembly	62828
Hinge assembly	62829
EPDM gasket*	63391
EPDM O-ring for lid**	62830
Neoprene O-ring for ring	32831



Hinged Lid shown open and closed

Lid Accessories and Repair Kit


Description	Part No.
2" MPT vent cap with poly screen	63266
2" MPT vent cap, anti-vortex, without screen	63316
3" MPT vent cap with poly screen	63845
Stainless steel screw for 8" and 16" rings	60081
18" lanyard for 8" lid and 16" non-hinged lid (tethers lid to tank)	62531
Strainer basket for 16" fill-opening (7" depth)	67374
Poly welding gun and rod	60221
Poly welding rod 30'	61879



Poly welding gun



Strainer basket



Lanyard

Valves & Couplers

Polypropylene Bulkhead Fittings / EPDM or Viton Gaskets

Description	Hole size required in tank for installation	Item Code	Part No.
1/2" heavy dity double threaded polypropylene fitting	1 7/16"	A	62834
3/4" double threaded polypropylene fitting	1 7/16"	A	60401
EPDM gasket for 1/2" and 3/4" (62834 and 60401)			60402
Type B Viton gasket for 1/2" and 3/4" (62834 and 60401)			60360
3/4" heavy duty double threaded polypropylene fitting	1 5/8"	A	62798
EPDM gasket 3/4" (62798)			62799
Type B Viton gasket for 3/4" (62798)			62800
1" double threaded polypropylene fitting	2 1/4"	A	60427
1 1/4" double threaded polypropylene fitting	2 1/4"	A	60403
1 1/4" anti-vortex polypropylene fitting	2 1/4"	D	63065
EPDM gasket for 1" and 1 1/4" (60427, 60403, and 63065)			60404
Type B Viton gasket for 1" and 1 1/4" (60427, 60403, and 63065)			60361
Anti-vortex adapter for 1 1/4" (60403)			62398
1 1/2" standard duty double threaded polypropylene fitting	2 1/4"	A	63931
EPDM gasket for 1 1/2" (63931)			63938
Type B Viton gasket for 1 1/2" (63931)			63939
1 1/2" double threaded polypropylene fitting	3"	A	60124
Siphon tube, 1 1/2" x 4 15/16" long			36382
Siphon tube, 1 1/2" x 12" long			63279
2" double threaded polypropylene fitting	3"	A	60405
2" double threaded 316 stainless steel fitting, less gasket	3"		61767
EPDM gasket for 1 1/2" and 2" (60124, 60405, 63481, and 61767)			60406
Type B Viton gasket for 1 1/2" and 2" (60124, 60405, 63481, and 61767)			60523
2" standard duty double threaded polypropylene fitting (maximum tank wall thickness = 3/8")	3"	E	63481
2" heavy duty double threaded polypropylene fittings	3 1/4"	B	63683
EPDM gasket 2" (63683)			60336
Type B Viton gasket for 2" (63683)			60008
Siphon tube, 2" short			60335
Siphon tube, 2" x 12" long			63262
2" MPT vent cap with poly screen			63266
2" MPT vent cap, anti-vortex, without screen			63316
Anti-vortex adapter for 2" bulkhead fitting			62399
2" polypropylene dust plug			60021
2" self-aligning double threaded polypropylene fitting (designed to install in dome of vertical tank above the liquid level)	4 1/2"		63668

Valves & Couplers

Polypropylene Bulkhead Fittings / EPDM or Viton Gaskets (Cont'd)

Description	Hole size required in tank for installation	Item code	Part No.
2" self-aligning double threaded polypropylene fitting (designed to install in dome of vertical tank above the liquid level)	4 1/2"		63668
EPDM gasket for 2" self-aligning (63668)			60331
Type B Viton gasket for 2" self-aligning (63668)			60351
3" double threaded polypropylene fitting (hex nut as shown in photo C)	4 1/2"	C	62299
EPDM gasket for 3" (62299)			60331
Type B Viton gasket for 3" (62299)			60351
2" polypropylene reducer for 3"			60331
Siphon tube, 3" short			60327
Siphon tube, 3" x 12" long			63263
3" MPT vent cap with poly screen			63845
4" double threaded polypropylene fitting (hex nut as shown in photo C)	5 3/4"		62171
EPDM gasket for 4" (62171)			62785
Type B Viton gasket for 4" (62171)			62786
Siphon tube for 4"			62714



A



B



C



D



E

Valves & Couplers

Bolted Fittings

Polypropylene Double Threaded Bolted Fittings / EPDM or Viton Gaskets

Bolted polypropylene fittings are equipped with 316 stainless steel bolts and come standard with EPDM gaskets. Viton gaskets are available as an option for the fittings.

Description	Item Code	Part No
3/4" polypropylene bolted fitting with ss bolts and EPDM gaskets	A	60502
1" polypropylene bolted fitting with ss bolts and EPDM gasket s	A	60505
EPDM gasket for 3/4" and 1"		60498
Type B Viton gasket for 3/4" and 1"		60355
1 1/2" polypropylene bolted fitting with ss bolts and EPDM gaskets	A	60513
2" polypropylene bolted fitting with ss bolts and EPDM gaskets	A	60516
EPDM gasket for 1 1/2" and 2"		60497
Type B Viton gasket for 1 1/2" and 2"		60356
3" polypropylene bolted fitting with ss bolts and EPDM gaskets		62471
EPDM gasket for 3"		62048
Type B Viton gasket for 3"		60602



A

Stainless Steel Single Threaded Bolted Fittings

Description	Part No.
2" 316 stainless steel single threaded bolted fitting less gasket	62847
EPDM gasket for 2" (1 required)	63206
Type B Viton gasket for 2" (1 required)	63225
Cross-linked polyethylene gasket for 2" (1 required)	62848
3" 316 stainless steel single threaded bolted fitting, anti-vortex, less gasket	63233
EPDM gasket for 3" (1 required)	63223
Type B Viton gasket for 3" (1 required)	63226
Cross-linked polyethylene gasket for 3" (1 required)	63043

Valves & Couplers

Bolted Fittings


Stainless Steel Double Threaded Bolted Fittings

Bolts are threaded into the back plate of the fitting so there are no welds or bolt holes that can be potential points of leakage. These fittings come standard without a gasket and require a single gasket that is installed on the inside of the tank. Available gaskets are cross-linked polyethylene, EPDM or Viton.

Description	Item Code	Part No
1/2" 316 stainless steel double threaded bolted fitting less gasket	B	63216
3/4" 316 stainless steel double threaded bolted fitting less gasket	B	63035
1" 316 stainless steel double threaded bolted fitting less gasket	B	62948
EPDM gasket for 1/2", 3/4", & 1" (1 required)		63205
Type B Viton gasket for 1/2", 3/4", & 1" (1 required)		63224
Cross-linked polyethylene gasket for 1/2", 3/4" & 1" (1 required)		62950
1 1/4" 316 stainless steel double threaded bolted fitting less gasket	B	63036
Cross-linked polyethylene gasket for 1/4"" (1 required)		63041
1 1/2" 316 stainless steel double threaded bolted fitting less gasket	B	63037
EPDM gasket for 1 1/4" and 1 1/2" (1 required)		63426
Cross-linked polyethylene gasket for 1 1/2" (1 required)		63042
2" 316 stainless steel double threaded bolted fitting less gasket	B	63038
EPDM gasket for 2" (1 required)		63206
Type B Viton gasket fpr 1 1/4", 1 1/2" and 2" (1 required)		63225
Cross-linked polyethylene gasket for 2" (1 required)		62848
3" 316 stainless steel double threaded bolted fitting less gasket	C	63039
EPDM gasket for 3" (1 required)		63223
Type B Viton gasket for 2" (1 required)		63226
Cross-linked polyethylene gasket for 3" (1 required)		63043
4" 316 stainless steel 8-bolt double threaded bolted fitting less gasket		63688
EPDM gasket for 4" (1 required)		63690
Viton gasket for 4" (1 required)		63691
Cross-linked polyethylene gasket for 4" (1 required)		63689



B



C

Valves & Couplers

Bolted Fittings

Bolted Ball Valve Replacement Parts

Item Code	Description	1/2" FP	3/4" FP	1" STD	1" FP	1-1/4" STD	1-1/4" FP	1-1/2" FP	2" STD	2" FP COM-PACT	2" FP	3" FP	4" FP	1-1/2" FPNZ	2" STD-NZ	2" FPNZ
A	stem screw	61347	61347	61347	61347	61347	-	-	-	-	-	-	-	-	-	-
B	stem cap screw & flat washer	-	-	-	-	-	61350	61350	61350	61350	61351	61351	61351	61350	61350	61351
C-1	yellow blank handle	61783	61783	61783	61784	61784	61785	61785	61785	61785	61786	61786	62838	61787	61787	61788
C-2	Norwesco blue handle	61721	61721	61721	61722	61722	61723	61723	61723	61723	61724	61724	62839	61725	61725	61726
D	Viton stem O-ring(s)	61497	61497	61497	61497	61497	61425	61425	61425	61425	61447	61447	62817	61425	61425	61447
E	valve stem w/ viton o-ring(s)	61359	61359	61359	61446	61446	61360	61360	61360	61360	61361	61361	62818	61360	61360	61361
F L M	stainless steel bolt, hex nut & lock washer	61421	61421	61421	61422	61422	61423	61423	61423	61424	61424	62208	62819	61423	61423	61424
G	end flange w/ flange seat	62051	62052	62053	62054	62055	62056	62057	62059	62316	62060	62065	62820	62057	62059	62060
G	male end flange w/ teflon seat	-	-	-	-	-	-	-	62064	62317	62063	62066	-	-	-	-
G	male coupler end flange w/ teflon seat	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
G	flanged end flange w/ teflon seat	-	-	-	62929	-	-	-	-	62930	-	62931	-	-	-	-
H	teflon seat	62077	62077	62077	62076	62076	62075	62075	62075	62074	62074	62073	62821	62075	62075	62074
I	large body EPDM o-ring seal	61378	61378	61378	61379	61379	61380	61380	61380	62319	61381	61382	62822	61380	61380	61381
J	valve body	61383	61383	61383	61384	61384	61385	61385	61385	62315	61386	61387	62823	61385	61385	61386
K	valve ball	61388	61388	61388	61389	61389	61390	61390	61390	62312	61391	61392	62824	61390	61390	61391
N	top flange w/ teflon seat for nozzle	-	-	-	-	-	-	-	-	-	-	-	-	62058	62061	62062
O	nozzle pipe	-	-	-	-	-	-	-	-	-	-	-	-	61400	61401	61401
P	seat o-ring	-	-	-	-	-	-	-	-	-	-	62114	-	-	-	-


Valves & Couplers

Bolted Fittings

Replacement Part Item Codes

Item Code	Description
G	flange end flange with teflon seat
H	teflon seat
I	large body EPDM o-ring seal
J	valve body
K	valve ball
L	stainless steel lock washer
M	stianless steel hex nut
P	seat o-ring

Item Code	Description
A	stem cap screw
B	stem flat washer
C	valve handle
D	viton stem o-ring(s)
E	valve stem with viton o-ring(s)
F	stainless steel bolt
G	end flange with teflon seat
G	male end flange with teflon seat
G	male coupler end flange with teflon seat



Valves & Couplers

Bolted Fittings

Multi-Port Ball Valve Replacement Parts

Size	Repair Kit- EPDM O-rings (3) and Teflon Seats (2)	Optional Repair Kit - Viton O-Rings (3)	T-Ball	Handles	Valve Stem with EPDM O-Ring
3/4"	61733	60438	60429	61735	60452
2"	60435	60442	60428	61736	60456

Single Union Replacement Parts

Size	Repair Kit- EPDM O-rings (3) and Teflon Seats (2)	Optional Repair Kit - Viton O-Rings (3)	Handles	Valve Stem with EPDM O-Ring
1/2"	60430	60437	60444	60451
3/4"	60431	60438	60445	60452
1"	60432	60439	60446	60453
1-1/4"	60433	60440	60447	60454
1-1/2"	60434	60441	60448	60455
2"	60435	60442	60449	60456
3"	60436	60443	60450	60457

Stainless Steel Valve Replacement Parts

Description	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	3"
Repair Kit	62374	62375	62376	62377	62378	62379	62380	62381
Handle	62369	62370	62370	62371	62371	62372	62372	62373

Cam Action Coupler Replacement Parts

Description	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	3"	4"
EPDM gasket	61570	61570	61571	61572	61572	61574	61575	62797
Key ring	61589	61589	61589	61589	61589	61589	61589	61589
Stainless steel pin	61582	61582	61582	61585	61585	61585	61584	61584
Stainless steel handle	61594	61594	61594	61595	61595	61595	61596	61596
Polypropylene shims	61715	61715	61716	61717	61717	61718	61719	-
Locking pin	-	-	-	63545	63545	63545	-	-

Valves & Couplers

Bolted Fittings

Y-Line Strainer Replacement Parts

Description	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	3"
EPDM gasket/o-ring	61452	61452	61750	61750	61561	61561	-
YLS w/o screen	61307	61309	61309	61748	61287	61288	62334
6 mesh screen	-	-	-	-	62306	62306	62231
12 mesh screen	-	-	-	-	62307	62307	62249
20 mesh screen	61449	61449	61749	61749	61508	61508	62252
40 mesh screen	61450	61450	61746	61746	61509	61509	62261
80 mesh screen	61451	61451	61747	61747	61510	61510	62400
EPDM body o-ring	-	-	-	-	-	-	62266
EPDM plug o-ring	-	-	-	-	-	-	62283
cap only w/plug & o-ring	-	-	-	-	61567	61567	62335

T-Line Strainer Replacement Parts

Description	1/2"	3/4"	1"
EPDM gasket	61537	61537	61537
TLS w/o screen	61283	61284	61285
20 mesh screen	61404	61404	61404
40 mesh screen	61405	61405	61405
80 mesh screen	61406	61406	61406