



celebrating  
50 years

1.800.665.4499  
barrplastics.com

# Septic & Sewage Holding Tanks

## Standard Belowground Tanks

### The Bruiser

This tough tank, made of corrosion and crack resistant components, can be used as a septic tank, holding tank, pump chamber, or cistern for potable water. It comes pre-plumbed and ready for installation up to 30" belowground. Uses native soils for backfill - no water needed, but it is recommended. Accepts 4" effluent filters and also features a watertight, domed, gasketed lid with stainless steel screws.



USG	IG	LTR	Part #	Diameter (in)	Length (in)	Height (in)	Lid/Fill Opening	Weight (lbs)
1000	833	3785	41736 (DC)	60	102	58	2-20	383
1250	1041	4732	41754 (DC)	55	116	66	2-20	468
1500	1249	5678	41774 (DC)	55	133	66	2-20	588

### One & Two Chamber Tanks



These environmentally safe & seamless one piece tanks are watertight and unaffected by soil chemicals and gases in sewage. Therefore, they are corrosion-resistant. They come pre-plumbed with PVC inlet and outlet assemblies and fit both 4" SCH 40 and SDR35 piping. Unlike the Bruiser, they cannot be used as pump out tanks and must be kept full at all times, or as soon as possible after pump out.

USG	IG	LTR	Part #	Diameter (in)	Length (in)	Height (in)	Lid/Fill Opening	Weight (lbs)
500	416	1893	41320 (SC)	51	101	42	1-20	174
1000	833	3785	41724 (DC)	60	102	58	2-20	323
1250	1041	4732	41746 (DC)	55	116	66	2-20	388
1500	1249	5618	41764 (DC)	55	133	66	2-20	483